SECTION 4 QUICK INDEX

P,	ige
PLIERS	1
PIPE TOOLS	9
WRENCHES	11
CLAMPS	27
SAW HORSES	30
VISES	32
BLACKSMITH'S TOOLS	39
SNIPS, TINNER'S	41
BLOW TORCHES	43
SOLDERING EQUIPMENT	47
THREADING TOOLS	
HAND DRILLS	94
BORING BITS	101
TWIST DRILLS	
REAMERS	127
SCREW EXTRACTORS	
WOODWORKING TOOLS	
POWER TOOLS	136
TOOL GRINDERS	174
ABRASIVES	177
LUBRICANT	188
FILES	205
MASON'S TOOLS	222

PLIERS, NIPPERS
WRENCHES, CLAMPS
VISES, FORGES, ANVILS
SOLDERING COPPERS
WELDING EQUIPMENT



TAPS, DIES, ETC.
BORING TOOLS
GRINDERS, OIL STONES
FILES, SANDPAPER
MASONS TOOLS

INDEX TO SECTION 4

HEAVY SLIP JOINT COMBINATION

KEEN WE KUTTER



Drop forged alloy steel, oil tempered. Pipe pattern jaws with milled teeth. Slip joint feature permits quick change for large and small work. Polished head, blue finished handles, with knurled grips.

Each			Lgth.,	Wt. box, lbs.	Each
F7184GK	(K51)	X1 D53★	6	1/2	\$2.30
F7185GK	(K51)	X1 D90★	8	3/4	2.85
F7186GK	(K51)	X2D30	10	11/4	3.45
		One in bo	ox.		

Thin Angle Nose Gripping

A super powerful gripping plier wrench with teeth set as in a Stillson wrench. Will not slip.

Drop forged from alloy steel. Heat treated. Jaws open up to ¾ inch. Polished head. Knurled handles.



Length 7 inches


Each			Each		
F7178GK	(K23/7)	X1D84★	\$2.75		

One in box. Wt. box 1/2 lb.

PLIERS

COMBINATION

SHAPLEIGH'S



Hardened forged steel. Polished nickel plated finish.

Each			Lgth.	in		Each
F3349G	(E1)	D6C6★	6	4	6	\$0.99
F3350G	(E2)	D9C0★	8	4	9	1.35

SHAPLEIGH'S



Hardened forged steel, cadmium finish.

г. і			Lgth.	in		Each
Each			ins.	ctn.	IDS.	Each
F3360G	(E18)	D5C3★	6	6	3	\$0.79
F3359G	(E17)	D7C0★	8	6	41/2	1.05

SHAPLEIGHS



Thin Nose

Hardened forged steel, polished nickel plated finish. Length 6½ inches.

Each			Each
	(E4)	D6C7	k
	Twelve	in ctn.	Wt. ctn. 6 lbs.

SHAPLEIGH'S



Bent Thin Nose

Hardened forged steel, polished nickel plated finish. Length 6½ inches.

Each			Each
F'3353G	(E5)	D8C3	★\$1.25
	Two i	n ctn.	Wt. cta. 5 lbs.

STAR * DENOTES BEST SELLER

CHROME PLATED SLIP JOINT PLIERS

Special analysis alloy steel. Designed to give maximum strength and shaped for their particular job. Knurled handles for a good firm grip. Short teeth are deeply milled and oil tempered for long wear. Hardened steel bolt. Chrome plated with full high lustre finish.

KEEN KUTTER



Combination-With Wire Cutter

Each			Lgth.		▲Each
F7196GK	(K160)	D9C3★	6	8	\$1.39
F7198GK	(K180)	X1D23★	8	10	1.85
F7206GK	(K1100)	X1D77	10	16	2.65
	(One in box			



Straight Thin Nose with Wire Cutter

			Lgth.,	Wt. Each	
Each			ins.	ozs.	▲ Each
F7195GK	(K150)	X1D03★	5	4	\$1.55
F7194GK	(K106)	X1D06	6	6	1.59
		One in bo	x		



Thin Bent Nose with Wire Cutter

Thirty degree offset nose. Especially valuable for use around the home.

Length 7 inches

-			THE PARTY OF THE P	
	Each			▲ Each
	F7197GK	(K165)	X1D33★	\$1.99
i	10 11 12 12 13 11 11 11 11 11 11 11 11 11 11 11 11		x. Wt. box 7 ozs.	



Combination Side Cutting

Electrically hardened cutting edge makes cutting of nails and wire easy.


Length 6 inches

Each			▲ Each
F7204GK	(K360)	X1D50★	\$2.25
	One in box	. Wt. box 8	ozs.

Shapleigh's Stocking Display

S 9-25-57

4-2-AA



FEATURES

- An assertment of selective Keen Kutter pliers and wrenches that are most popular in the field.
- A display unit of superior construction made of top grade fir plywood painted yellow with chrome stripping. Size 24" x 24".
- A sturdy wire easel which permits it to stand on your counter, in your window, or may be displayed on a wall.

Here is a well designed modern display to increase your sales and your profits on Pliers and Adjustable Wrenches

HOLDS TWO EACH:

TOOL NOS.		Retail Price Each	TOOL NOS.	Retail Price Each
F7171GK	6" Combination Slip-Joint Pliers	. \$.80	F7145GK 61/2" Utility Rib-Joint Pliers	. \$2.20
F7172GK	8" Combination Slip-Joint Pliers	. 1.20	F7187GK 10" Utility Rib-Joint Pliers	
F7183GK	7" High Leverage Diagonal Pliers .	. 3.20	F7189GK 6" Long Chain Nose	
F7181GK	5" Diagonal Pliers	. 2.90	Side Cutting Pliers	. 3.25
F7182GK	6" Diagonal Pliers	3.30	F7188GK 6" Long Chain Nose Pliers	. 2.55
F7191GK	7" Electrician's Standard		F7890GK 4" Adjustable Wrenches	. 2.40
	Side Cutting Pliers	. 3.45	F7891GK 6" Adjustable Wrenches	2.40
F7192GK	8" Electrician's Standard		F7892GK 8" Adjustable Wrenches	. 2.75
	Side Cutting Pliers	. 3.80	F7893GK 10" Adjustable Wrenches	. 3.55
F7209GK	10" Fence Pliers	. 3.10	F7894GK 12" Adjustable Wrenches	. 5.20

Order As FX-KK17GK

Degler Cost - X65D40

Total Retail Value \$98.10



Packed 1 Display with Tools Per Carton, Wt. Ctn. 26 Lbs.

The Recollection of QUALITY Remains Long After the PRICE is Forgotten"

PLIERS

KEEN KUTTER

Diagonal Cutting

Properly designed for all-around cutting.

Drop forged steel, finely tempered. Handhoned cutting edges. Polished head, blue finish handles, with scored grips.



				Wt.	
Each			Lgth., ins.	lbs.	Each
F7181GK	(K45/5)	X2 D03★	5	1/4	\$3.05
F7182GK	(K45/6)	X2D33★	6	1/2	3.50
	(One in box			



Giant Diagonal Cutting

Very high leverage for easy cutting. Full fashioned handles.

Drop forged alloy steel, oil tempered. Fine cutting edges. Polished head, blue finish handles, with scored grips.

Length 7 inches Each Each F7183GK (K47/7) X2D27★ \$3.40 One in box. Wt. box 3/4 lb.



Oblique Cutting

For close cutting in confined places. Cuts through silk insulation. Also used by shoemen for cutting out shoe buttons, nails, etc. For electricians, telephone men and switchboard builders. Cuts close, the narrow head permitting its use in confined places. Perfectly fitting knives meeting at all points. Blued finish handles. Polished head and jaws. Oil tempered and honed raised cutting edges. Encased lap joint. Reinforced with two heavy side plates.

Regular Pattern-Length 6 Inches Each ▲ Each F7118G (202/6) X2D33..... . \$3.50 One in box. Wt. box, 1/2 lb.

PLIERS **ROUND NOSE**

KEEN WE KUTTER



Long Chain Needle Nose

Has spring-tempered needle nose. Finely balanced for delicate work. No cutter.

Drop forged alloy steel, properly tempered. Face of jaws scored. Polished head, blue finish handles, with knurled grips.

	Lengt	h 6 inches	
Each			Each
F7188GK	(K66/6)	X1 D80★	.\$2.70
	One in box.	Wt. box 1/4 lb.	



Long Chain Nose-Side Cutting

Drop forged alloy steel, properly tempered. Face of jaws scored. Polished head, blue finish handles, with knurled grips.

	Lengt	h 6 inches
Each		Each
F7189GK	(K76/6)	X2D30★\$3.45
	One in box.	Wt. box 3/8 lb.

CHAMPION DE ARMENT



Long Nose With Side Cutter

Channel Lock

Polished steel finish. Knurled grips. Length 6 inches. Point 3/32 in. round.

Each		▲Each
F7124G	(326)	▲Each X2D26\$3.40
		octo Wt ctn 2 lbs

COMBINATION CEE TEE CO



Forged from special analysis steel, carefully machined, hardened and oil tempered. Sharp milled teeth. Nuts and bolts turned from solid bar of steel and case hardened. Lustrous bright plated finish.

			Lgth.		Wt. Box.	
Each			ins.	Box	lbs.	▲Each
F7173G	(H25B)	D5C3★	5	12	21/2	\$0.80
F7174G	(H26B)	D5C3★	6	12	6	.80
F7175G	(H28)	D8C0	8	1	3/4	1.20
F7176G	(H210)	X1D13	10	1	1	1.70

SLIP JOINT



Carefully heat-treated steel pipe pattern jaws with milled teeth. Wire cutter. Special lock nut. Knurled handles. Nickel plated finish.

welve in	6 ctn.	5	\$0.85
		3	1.25
	D8C3	welve in ctn. D8C3 8 Six in ctn.	D8C3 8 3

UTICA



High quality steel, carefully heat treated. Pipe pattern jaws with milled teeth. Wire cutter. Special lock nut. Nickel plated finish. Length 6 inches.

Each		▲ Each
F7141G	(5/6)	D4C3*\$0.65
		e. Wt. each 2 ozs.

PLIERS SLIP JOINT



High quality steel, carefully heat treated. Pipe pattern jaws with milled teeth. Wire cutter. Special lock nut. Knurled handles Nickel plated finish. Length 6 inches.

Each		▲ Each	
F7103G	(7/6)	D5C4★ \$0.81	
		in ctn. Wt. ctn. 4 lbs.	

SLIP JOINT-THIN NOSE



High quality steel, carefully heat treated for strength and lasting service. With wire cutter and sharp gripping teeth. Bright nickel plated finish.

Length 61/2 inches.

Each			Each
F7212G	(P161/2)	D2C3*	\$0.35
	Twelve in	box. Wt. box 4 lbs.	

UTILITY COMBINATION PLIERS

KEEN KUTTER



Drop forged alloy steel with full forged ribs for added strength. Milled teeth. Gun metal finish with polished head and side.

Capacity Opening Approximately 1 inch

Each			Each
F7145GK	(K507/61/2)	X1D57	\$2.35
(One in box. Y	Wt. box 6 ozs.	

COMBINATION PUMP PLIERS AND WRENCH

KEEN KUTTER




Drop forged alloy steel with full forged ribs for added strength where needed. Milled teeth. Gun metal finish with polished head and sides.

Capacity 3/6 to 13/8 inches. Length 91/2 inches.

Each			Each
F7187GK	(K57)	X2D10★	\$3.15
	One in	box. Wt. box 1 lb.	

COMBINATION PUMP PLIERS AND WRENCH



Thin jaws will reach hard-to-get-at water pump and other nuts on cars and trucks. Drop forged steel, cadmium finish. Plain handles. Milled teeth. Length 9¾ inches.

Each			Each
F7144G	(9100)	D80	5\$1.25
	One in	box.	Wt. box ½ lb.

CHANNELLOCK

Self-Gripping

A new revolutionary powerful gripping Channellock design. The tongue and groove Channellock joint provides a vise-like grip entirely independent of the gripping power of the user's hand.


Highest grade alloy steel, properly heat treated. Polished steel finish. Handles have knurled grips. Thoroughly tested beyond intended capacity.



Will hold work of any shape with a positive pipe wrench grip. Will exceed a pipe wrench in usefulness. Streamlined and light in weight.

Four adjustments. Length 91/2 inches. Capacity 3/6 to 11/8 inches.

1	Each			▲ Each 26\$3.40
i	F7128G	(410)	X2D	26\$3.40
				Wt. ctn. 6 lbs.



Pump

The wide range of adjustments makes this plier adaptable to a multitude of uses.

Channellock adjustment eliminates wear on the joint bolt.

Five adjustments. Length 91/2 inches. Capacity 3/6 to 15/8 inches.

Each			▲ Each		
F7133G	(420)	X2D15-	\$3.00		

Six in box. Wt. box 43/1 lbs.

STAR * DENOTES BEST SELLER

PLIERS ROUND NOSE

KLEIN



Long Nose, Side Cutting

Blued finish handles. Polished head and jaws. Forged from special grade tool steel. Ground and tempered. Raised cutting edge. Scored jaws. Point 1/2 inch round.

Each			Lgth.,	Wt. box, lb.	Each
F7120G	(203)	X2D40★	6	3/8	\$3.60
F7119G	(203)	X2D60	7	1/2	3.90

One in box

KLEIN



Long, Needle Nose. Without Wire Cutters

Polished head and jaws. Blued finish handles. Highest grade tool steel. Tempered and hardened so that jaws will not spring when pressure is applied. Long reach which permits getting into difficult places. Adapted for stripping the ends of insulated wire. A very popular pattern for electricians and general mechanics.

Length 6 inches. Point 1/16 inch round.

Each		Each
F7125G	(303)	X2D07★ \$3.10
	One in	box. Wt. box 3/8 lb.

PLIERS ROUND NOSE KLEIN



Milliners' or Radio


Long Curved Nose. Without Wire Cutters

Blued finish handles. Polished head and jaws forged from special grade tool steel. Scored jaws. Long curved nose especially adapted for switchboard work or for reaching into confined places. Long curved nose bent at 45 degree angle. Length 6 inches.

Each		Each
F7201G	(302/6)	X2D53\$3.80
	Six in box	x. Wt. box 15/8 lbs.

FLAT NOSE

KEEN AL KUTTER



Long slender nose for motor winders and radiator repair men.

Drop forged alloy steel with spring tempered nose. Polished head. Properly balanced and smoothly finished.

Length 6 inches Each F7193GK (K86/6) X1D87.....\$2.80

F7193GK (K86/6) X1D87...... \$2.80 One in box. Wt. box ½ lb.

PARALLEL ACTION BERNARD



Nickel plated and polished tool steel. Open throat. Parallel jaws, scored. Heavy sealed hollow handles riveted to jaws. Tempered and honed top cutter. Rivet joint. Knurled grips.

			Lgth.,	Wt.	
Each			ins.	lbs.	▲ Each
F7106G	(102/51/2)	X2D11	$5\frac{1}{2}$	3	\$3.15
F7107G	(102/61/2)	X2D51★	61/2	31/2	3.75
F7108G	(102/8)	X3D27	8	$4\frac{1}{2}$	4.90
	One in bo	x, six boxe	s in cti	1.	

STAR * DENOTES BEST SELLER

PLIER ASSORTMENT

FULLER



Made to U. S. Government specifications Electronic induction treated jaws. Completely ground and polished from top to bottom.

Hand honed cutting edges. High leverage handles.

Individually carded and pre-priced.

Consists of:

Qty.	No.	Type	Size in.
2	190	Diagonal Cutting	5
2	190	Diagonal Cutting	6
2	192	Long Nose	51/2
2	192	Long Nose	61/6
2	194	Lineman's Side Cutter	7
2	194	Lineman's Side Cutter	8
	N	Ietal Rack—Free	

Can be mounted on peg board or wall.

Per Asst.		Per Asst.
0-198-G	X15D73	\$24.84

One asst. in ctn. Wt. ctn. 6 lbs.

OPEN STOCK Diagonal Cutting

Each			Size, in.	Wt. Box, lbs.	Each
7165G	(190-5)	X1 D25	5	34	\$1.98
7166G	(190-6)	X1 D25	6	1	1.98
		Long No	se		

7167G (192–51%) X1D25 51/3 5/8

111010	(132-372)	NI DEG	0/2	/8	1.00
F7168G	(192-61/2)	X1D25	61/2	1/2	1.98

Lineman's Side Cutter

F7169G	(194-7)	X1 D39	7	11/4	2.20
F7170G	(194-8)	X1 D46	8	11/2	2.30
	One or	card, two	in bo	x	

PLIERS



Standard—Side Cutting

An ideal tool for electrical construction work. Unsurpassed cutting qualities.

Drop forged alloy steel, skillfully tempered. Face of jaws scored. Polished head, blue finish handles, with knurled grips.

Each		Lengt inch	ch, es	Weight Box, lb.	Each
F7190GK	(K85/6)	X2D10	6	1/2	\$3.15
F7191GK	(K 85/7)	X2D40	7	3/4	3.60
F7192GK		X2D63★ One in box	8	1	3.95



Giant Button's Pattern

Has four wire cutters-two between jaws and one each top and bottom of head. The cutters between jaws hold one end of the wire firmly after being cut.

Drop forged alloy steel, oil tempered. Face of jaws scored. Polished head, blue finish handles, with smooth grips.

Each		Length, Weight inches Box, lbs. Each			
F7210GK	(KB8)	X2 D03★	8	1	\$3.05
F7211GK	(KB10)	X2D40★	10	11/2	3.60
	C	ne in box			

ELECTRICIANS' OR LINEMENS' | ELECTRICIANS' OR LINEMENS' | ELECTRICIANS' OR LINEMENS'

KLEIN STANDARD



Side Cutting. For Bare and Insulated Wire

Blued finished handles. Polished head and jaws. Hand forged from a special grade tool steel. Oil tempered and honed cutting edge. Extra heavy rivet joints. Scored jaws. Round nose permits easier working in confined space. All edges are rounded to prevent nicking of wire.

Narrow End Streamlined

(201 NE)

	Length		
	ins.	Ctn., lbs.	Each
X2D77	6	33/4	\$4.15
X3D07★	7	35/8	4.60
X3D47★	8	57/8	5.20
X3D90	9	63/4	5.85
	X2D77 X3D07★ X3D47★ X3D90	x2D77 6 x3D07★ 7 x3D47★ 8	X2D77 6 3¾ X3D07★ 7 35% X3D47★ 8 5¾

One in box. Six boxes in ctn.

Heavy Blunt Head

(201)

		Lengtl	ı, Wt.	
Each		ins.	Ctn., lbs.	Each
F7110G	X3D07	7	35/8	\$4.60
F7111G	X3D47	8	57/8	5.20
F7112G	X3D90	9	7	5.85

One in box. Six boxes in ctn.

KLEIN STANDARD



Side Cutting. With Sleeve-Joint Twister For Bare and Insulated Wire

Blued finished handles. Polished head and jaws. Hand forged from a special grade tool steel. Oil tempered and honed cutting edges. Extra heavy rivet joint. Scored jaws. Sleeve opening in 7-inch for Nos. 14 and 17NBS and 12 BTS. 8 inch for Nos. 12 NBS and 10 BTS wire.

		(212)		
Each			., Wt. Ctn., lbs.	Each
F7122G	X3D23	7	35/8	\$4.85
F7123G	X3D67★	8	57/8	5.50
	One in box.	Six boxe	es in ctn.	

GLASS PLIERS RED DEVIL



Forged from high grade tool steel. Flaring wide jaw. Rugged and nicely balanced. Full polished finish. Length 8½ inches.

Each ▲ Each F7129G (410) X5D10..... ., \$8.50 Six in box. Wt. box 5 lbs.

PLIER BOLTS



With Nuts For Slip Joint Pliers

Polished Steel

			For Pliers,	
Each			inches	▲ Each
F7057G	D0C7	(EB5)	5	\$0.15
F7058G	D0C7	(EB6)	6-7-8	.15
F7060G	D0C9	(EB10)	10	.15

Loose. Average wt. each 1/2 oz.

PLIER HANDLES



Never Slip

Applied simply by driving them on the plier handles. No heating or soaking.

Colorful plastic, moulded to fit plier handles snugly. Half smooth, half knurled for solid grip.

Non-Burning Non-Explosive

			For	Wt.	
D4C0%			Pliers	Box.	Per
Per Pair			inches	lbs.	Pair
F7219G	D3C9	(PG6)	5 & 6	11/2	\$0.65
F7220G	D4C2★	(PG7)	7	21/4	.70
F7221G	D4C5★	(PG8)	8 & 9	3	.75
	Twel	ve pair i	n box		

SIDE CUTTING PLIERS

KLEIN

High Leverage

Eliminates extra hinging and has comfortable one-hand operation.

Cuts through weatherproof hard-drawn solid wire up to No. 2.

Forged from high grade tool steel, individually fitted, tempered, adjusted and tested.

Length 9 inches



Blunt Head Standard

Each		Each
F7138G	(213/9)	X4D40\$6.60
	Six in pl	kg. Wt. pkg. 14 lbs.



Narrow End Streamlined

Each		Eac	h
F7139G	(213-NE9)	X4D40\$6.6	0

Six in pkg. Wt. pkg. 131/2 lbs.

PLIER AND NIPPER DISPLAY ASSORTMENT

FULLER



Four each of the following drop-forged tools with stove-baked enamel handles, polished ground heads, heat-treated jaws and sharp cutting edges in attractive counter display box:

No.	Description	
64	End Cutting Nippers, 6 inch	
60	Engineers Pliers, 7 inch	
74	Long Nose Pliers, 6½ inch	
Per .	Asst.	Per Asst
F716	50G (119) X9D52	\$14.2
	One asst. in box. Wt. box 5	lbs.

OPEN STOCK PLIERS FULLER



Engineers' All-Purpose

Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

	Length 6 inches	
Each	(70) - 5700	Eacl
F/162G	(70) D7C9	\$1.19
	Four in box. Wt. box 134 lbs.	



Long Nose Side-Cutting

Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

	Length 61/2 inches
Each	Eacl
F7163G	(74) D7C9 \$1.19

END CUTTING NIPPERS



Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

District Co.	Length 6 inches	
Each		Each
F7161G	(64) D7C9	\$1.19
	Four in box Wt box 13/ the	

PLIERS

FULLER

Insulated—DeLuxe

Long Nose Side-Cutting



Made in England to U. S. government specifications. Withstands 1,000 volts.
Individually carded.

Each		Each
F7156G	(184)	X1D47\$2.20
	Six in	ctn. Wt. ctn. 41% lbs

SIDE CUTTING PLIERS

High Leverage

Eliminates extra hinging and has comfortable one-hand operation.

Cuts through weatherproof hard-drawn solid wire up to No. 2.

Forged from high grade tool steel, individually fitted, tempered, adjusted and tested.

Length 9 inches



Blunt Head Standard

Each		Each
F7138G	(213/9)	X4D40\$6.60
	Six in p	kg. Wt. pkg. 14 lbs.



Narrow End Streamlined

		Eac
F7139G (21	13-NE9))	(4D40\$6.6

Six in pkg. Wt. pkg. 131/2 lbs.

PLIER AND NIPPER DISPLAY ASSORTMENT

FULLER




Four each of the following drop-forged tools with stove-baked enamel handles, polished ground heads, heat-treated jaws and sharp cutting edges in attractive counter display box:

64	End Cutting Nippers, 6 inch
60	Engineers Pliers, 7 inch
74	Long Nose Pliers, 6½ inch
Per	Asst. Per Ass
F71	60G (119) X9D00\$14.2
	One asst, in box, Wt. box 5 lbs.


Description

OPEN STOCK PLIERS FULLER



Engineers' All-Purpose Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

Length 6 inches Each (70) D7C5. F7162G Four in box. Wt. box 134 lbs.



Long Nose Side-Cutting

Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

Length 61/2 inches Each (74) D7C5.. F7163G Four in box. Wt. box 1 lb.

END CUTTING NIPPERS FULLER



Drop-forged with stove-baked enamel handles, polished ground head, heat-treated jaws and sharp cutting edges.

Length 6 inches Each \$1.19

PLIERS

7-15-59

FULLER

Insulated—DeLuxe Long Nose Side-Cutting



Made in England to U. S. government specifications. Withstands 1,000 volts. Individually carded.

Each Each F7156G (184) X1 D39...... \$2.20 Six in etn. Wt. ctn. 41/2 lbs.

CARPENTERS' PINCERS

KEEN A KUTTER



Forged from highest grade tool steel. Heavy steel rivet at joint. Oil tempered jaws with inside bevel. Polished face. Red handles.

			Length,	Wt. Box,	
Each			ins.	lbs.	Each
F7013GK	(K706)	X1D20★	6	1/6	\$1.80
F7014GK	(K708)	X1 D33★	8	1	2.00
	The state of the s		The same of the sa		

One in box

SHAPLEIGHS



Nail Cutting

Polished jaws. Black finish handles. Forged from high grade too steel. Oil tempered jaws. Steel rivet joint.

Each			Length, ins.	lbs.	Each
F7028G	(SN10)	X1D84	10	91/2	\$2.75
F7029G	(SN14)	X2D20★	14	121/2	3.30
		Siv in	hov		

END CUTTING NIPPERS

KEEN KUTTER



Bulldog

A strong, easy cutting tool for body builders, fender repair men and other mechanics who require a high quality end cutting nipper that

Forged from fine grade alloy steel carefully tempered with fine cutting edges. Good leverage. Polished head, blue finish handles, with

checkered grips.

Each F7179GK F7180GK		Length, ins. 6 7	Wt. Box, lbs.	Each \$3.50 3.95
	One	in box		

TODDS



Handles and head, natural oil finish, with polished head. Highest grade tool steel cutters, finely tempered, sharpened and tested. Set screw in handle for accurate adjustment of cutting edges. Cutters are interchangeable, easily removed, sharpened and replaced.

Each			Width Cut, ins.	Length, ins.	Wt. Pkg., ozs.	Each
F7024G	(N6)	X3D05	11/16	6	10	\$4.55
F7023G	(N4)	X3D25★	13%	8	15	4.85
F7022G	(N3)	X3D55★	19/16	10	26	5.30
F7021G	(N1)	X4D15	134	12	34	6.25
		200		12		

Wrapped one in pkg. **EXTRA CUTTERS**

With Screws

Per Pair F7063G	(NC1)	X1 D35	Width Cut, ins. 134	For Nos. N1	Wt. Env., ozs. 2	Per Pair \$2.00
		One pair i	in envelope, w	ith screw	5	

FENCING PLIERS OR STAPLE PULLERS

KEEN KUTTER



Length 101/4 inches X2D17★... One in box. Wt. box 13% lbs. F7209GK (K1946)

CRESCENT



Combination staple puller and wire stretcher with two wire cutters. Broad face on head for driving staples.

Forged steel. Polished head. Gun metal knurled handles. Length 101/2 inches.

Each F7130G (1936) X2D56★... One in box. Wt. box 1½ lbs.


CRESCENT



Forged steel. Double hammer head with faces hardened and checkered. Wire stretcher, wire splicer, staple puller and two cutters. Black finish. Knurled handles. Length 10 inches.

F7137G (1907) X2D43... One in box. Wt. box 1¼ lbs. .. \$3.65

LINEMEN'S WIRE GR!PS



Havens Grips Forged from crucible tool steel. Galvanized finish. The eccentric, or dog, is hand cut, hardened and tempered. All rivets are steel, machine turned. Maximum opening, 1½ inch (.53) inch. Minimum opening finch (.14) inch. For ½ inch wire and smaller. Safe capacity, 5000 lbs.

Each X4D40... F496G (1604/20) .\$6.75 One in box. Wt. box 21/2 ibs.

WIRE CUTTERS PORTER HAND KLIP



For cutting and repair jobs on the farm, ranch, orchard, mine, reservations, in the home and camp. Also for clearance and maintenance work by utilities, railroads, car shops, garages, etc.

Tough alloy steel cutting head, drop forged and heat treated. Specially designed parrot-beak jaw with protruding tip. Finest pressed steel handles, scientifically shaped to fit the palm and fingers, covered with a special plastic moulding, pliable, durable and non-tacking.

Cutting capacity—wire rope and soft rods up to % inch, annealed bolts in threads up to ¼ inch. Length over all 8 inches.

Each		Handy and Useful	▲ Each
F7091G	(6C)	X4D80★	\$7.20
	25 17	Loose. Wt. each 1 lb.	

BOLT CLIPPERS

PORTERS

Forged tool steel adjustable jaws. Red malleable iron curved handles with improved hand grip. Metal handle stops with rubber buffers. Spring control. Tempered carbon steel straps. Bushing in center joint. All bolts heat treated. Compound lever action.



Rigid Clipper Cutter

Cutting edges beveled almost entirely from one side.

For close cutting non-ferrous metals, wrought iron, annealed bolts in the thread, soft steel, cold-drawn screw stock, machinery steel, annealed tool steel and stainless iron.

Each			ength,		Cuts Soft Rods, inches	Weight Each, lbs.	▲ Each
F7086G	X8D15★	090	18	3/8	5/16	41/4	\$12.20
F7083G	X10D10★	190	24	7/16	3/8	63/4	15.10
FX-2B-G	X12D95	290	30	9/16	1/2	101/2	19.40
FX-3B-G	X16D80	390	36	5/8	9/16	1434	25.20
			L	oose			

Rigid Clipper Cutter

Cutting edge beveled almost entirely from one side.

For all-around work in softer metals requiring close cutting. Cuts bolts in the thread up to 1/2 inch. Soft rods up to 1/2 inch, Length 14 ins. Each

Each

F7092G (1490) X7D67 ... \$11.20

	E	xtra Jaws For At	ove
Each			▲ Each
F7034G	(1412-Right)	X1D87	\$2.80
F7035G	(1412-Left)	X1D87	2.80


Loose. Wt. each 1/4 lb.


PORTER'S UTILITY CUTTER

A small clipper designed for the occasional user.

Length 12 inches. Cuts bolts up to ½ inch. Cuts soft rods up to 3/16 inch.

Each		(1290)	▲ Each
F7093G	X4D60★		\$6.90
One	in display	ctn. Wt. ctn. 11/2 lb	s.






BOLT CLIPPER REPAIR PARTS

PORTER

Japanned malleable iron handles with orange colored grips. Tempered steel detachable clipper cut jaws. Rubber buffers. No adjusting sections are provided to compensate for wear, some adjustments may be made by filing stops between handles. Powerful toggle action. All parts interchangeable.

In Ordering Repair Parts Give Name and Number of Part as Well as Number of Clippers.

Clipper		No090-	-18 inch	N	o190—2	4 inch		No	-2903	0 inch		N	lo390—	-36 inch	
Name of Part	No. of Part		Weight Ea., lbs.	No. of Part		Weight Ea., lbs.	▲ Each	No. of Part		Weight Ea., Ibs.	▲ Each	No. of Part		Weight Ea., lbs	▲ Each
Clipper cut jaws, right hand Clipper cut jaws, left hand	F7036G-01 F7037G-02	X2D03 X2D03	14	F7038G-11 F7039G-12	X2D40 X2D40	1½8 1½8		F7040G-21 F7041G-22	X3D10 X3D10	21/8 21/8		F7042G-31 F7043G-32	X3D90 X3D90	2 9/16 2 9/16	\$5.80 5.80



STAR * DENOTES BEST SELLER

PIPE VISES

RIDGID

Bench Yoke



Malleable iron frame and base. Machine milled steel screw and cross arm. Frame hinged at side. Hook holds frame rigid when closed. Convenient pipe rest and bender. Highest quality long grip tool steel jaws. Red yoke with black base.

Capacity each, Each Each pipe, ins. lbs \$18.50 0-BY2A-G X12D35 1/8 to 2 111/2 Loose

COLUMBIAN



Extra strong, high grade malleable frame and iron bases, with easyworking, unbreak-able self - locking hook. Steel jaws, carefully heattreated. Reversible lower jaws milled on both sides. Cold rolled steel screw and cross handle with forged ball ends. Handy bender for small pipe, conduit and tubing. Flat base has 3 holes for mounting on any plane surface.

Long Bearing Jaws

ns Each Each 0-160-G X12D35 to 2 94 41x54 9 \$18.50 0-161-G X14D60 \$\frac{1}{2}\$ to 2\frac{1}{2}\$ 10\frac{1}{2}\$ 5\frac{1}{2}\$ 5\frac{1}{2}\$ 11 21.90 +163-G X28D80 \$\frac{1}{2}\$ to 4\frac{1}{2}\$ 14\frac{1}{2}\$ 6\frac{1}{2}\$x9 26 43.20

Interlocking Jaws +164X-G X64D70 1 to 6 171 78x101 37 97.50

Loose

LITTLETOWN Plumbers Broad Jaw Type



Constructed of malleable iron.

Specially designed, enalling all styles of pipe. including polished or brass, to be firmly held with least possible damage. Long one-piece removable grooved steel jaws. Selflocking latch.

Heil Closins. Size Bas ins. Wei ▲ Each 8 4x5 5½ \$6.00 0-20C-G X4D05 ★ 1/8×2 0-300-G X6D00 1/x21/2 9 61/2x5 81/2 9.00 F7094G (9555) X1D75★...

CHAIN PIPE VISES RIDGID



Bench

Special malleable frame. Highest quality tool steel jaws, hardened for long wear. Handy pipe rest and bender. Steel flat link chain.

Capacity Wt. pipe, each, Each ins. lbs. Each 0-BC2-G X9D10★ 1/8 to 2 51/2 \$13.65 Loose

THIN WALL TUBE CUTTERS

GENERAL Pocket Size

Ideal for garage, oil burner and refrigeration servicemen for cutting all thin wall tubing up to I inch outside diameter. This perfectly balanced precison tool assures fast, easy cut-

ting with practically no burr.

Fine quality material, rust-proof finish. Extra thin razor-edged wheel. Sliding spring lock safety reamer with two bevel machine ground cutting edges. Spring lock holds reamer back out of the way when not in use. Length closed 4½ inches.

Each F7101G (TC100) X1D04★..... One in box. 12 in ctn. .\$1.56 Wt. box 1/2 lb.

FLARING TOOLS IMPERIAL



Flares soft copper, brass or aluminum tubing to make up S. A. E. 45% flare joints without cracking or splitting tubing.

Yoke of steel forging. Swivel type flaring cone, which remains stationery when compressor screw is turned.

Flares 3/6, 1/4, 1/6, 3/8, 1/6, 1/2, and 1/8 in. O. D. Tubing.

Each Each F7102G (296FS) X4D18... \$5.95 One in box. Wt. box 134 lbs.



Flures copper, brass and aluminum tubing without cracking or splitting.

Steel forging compressor with cadmium finish. Tool can be used without removing tubing from equipment. Hinged die. One end opens for rapid application. Holes threaded for secure grip.

Flares 3/16, 1/4, 5/16, 3/8, 7/16, 1/2 and 5/8 inch Tubing

Each (290) X2D31★..... One in box. Wt. box 2 lbs. F7090G ..\$3.50

TUBE CUTTERS NATIONAL



Pressure rollers operate on a sliding feed mechanism and cutter wheel is mounted on a wide axis. Perfect alignment guaranteedthreading eliminated. Retractable vet locks solidly open. Die cast aluminum body. Steel

blade and reamer knife easily replaced. Length over all closed 4 inches. Width 2 inches. Tubing capacity 0 to 1 inches O.D

One in box. W t. box 71/2 ozs.

Items marked - not carried in stock. Can only be furnished by shipping direct from factory, F. O. B., Cleveland, Ohio. Freight allowed on shipments of X150D00 or more.

PIPE WRENCHES

KEEN WEEK KUTTER




Stillson Pattern

Highest grade drop forged tool steel. Polished shank jaws. Malleable frame zinc finished. Solid steel red finish handle and nuts. Heavy steel springs.

Each		Lgth.,	Adj.,		Each
2.0.01	(KX6)			
F7928GK	X1D30	6	1/8 to 1/2	3	\$1.95
	(KX8)			
F7929GK	X1 D50★	8	1/8 to 3/4	6	2.25
	()	(X10)			
F7930GK	X1D95★	10	1/8 to 1	12	2.95
	(1	(X14)			
F7931GK	X2D65★	14	1/4to11/2	18	4.00
	(1	(X18)			
F7932GK	X3D75	18	1/4 to 2	36	5.65
	(1	(X24)			
F7933GK	X6D50	24	1/4to11/2	60	9.85
	Six in	wood	box		100

MASTER STILLSON



Drop forged tool steel. Polished shank and jaws. Polished malleable frame. Steel drop forged paneled handles, painted red. Lengths 6 and 8 inches have front springs, lengths 10 and 14 inches have two back springs and one front spring. Lengths 18 and 24 inches have two back springs and one front spring. Lengths 36 and 48 inches have single front spring.

				Wt.	
Each			Adj. ins.	Box,	Eich
		(PS8)			
F7935G	X1D50	8	1/8 to 3/4	6	\$2.25
	(PS10)		
F7936G	X1D95	10	1/8 to 1	12	2.95
	(1	PS14)		
F7937G	X2D65	14	1/4 to 11/2	18	3.95
	(1	PS18)			
F7938G	X3D75	18	1/4 to 2	36	5.65
	(PS24)		
F7939G	X6D50	24	1/4 to 21/2	60	9.75
FX-PS36-G	X13D75	36	1/4 to 31/2	90	20.75
6 through		six in in bdl		nch s	ix

HEAVY DUTY PIPE WRENCHES

KEEN WITTER



Malleable Alloy

Will take roughest treatment. Better balanced "feel", fast easy adjustment, calibrated hook jaw and patented double action spring makes these wrenches bit, ratchet and release faster. Pearlitic malleable alloy. Forged steel jaws milled and triple heat treated. Red handle with hang hole.

Each		Lgth.	in.	Pkg. lbs.	Each
F7922GK	X1D98	8	1/8-1	6	\$3.15
F7925GK	X2D58	10	1/8-11/2	12	4.15
F7923GK	X3D01	12	1/8-2	18	4.80
F7926GK	X3D48	14	1/4-2	21	5.55
F7927GK	X4D98	18	1/4-21/2	33	7.95
		Six in	Pkg.		34-1

RIDGID




Alloy steel polished and hardened jaws. Inserted steel jaws.

Knurled adjusting nut. Japanned finish handle. The inserted jaw and frame are fastened to handle by a removable steel pin. Removable jaws and nut have round top and bottom thread.

Each		ength,	ap.,	Vt. Box	Each
Each	(1.0.1	1 2 2	isacii
	(RPW				
F7944G	X1D80	6	3/4	3	\$2.70
	(RPW	8)			
F7945G	X2D10	8	1	41/2	3.15
	(RPW1	(0)			
F7946G	X2D75★	,	11/2	9	4.12
	(RPW1		, 2		
F7950G	X3D20★	,	91	18	4.80
113000			21	10	T,00
	(RPW1	,		-	
F7947G	X3D70★	14	2	191/2	5.55
	(RPW1	8)			
F7948G	X5D30★	18	21/2	303/4	7.95
	(RPW2	(4)			
F7949G	,	,	3	51	12.50
FX-RPW36-G					-
FX-RPW48-G				28	
FA-NFW40-G	A20D30	40	0	20	09.70
6 thro	ugh 24-incl	h, si	x in l	box	

PIPE WRENCH REPAIRS



KEEN KUTTER and SHAPLEIGH'S

Front Jaws

-		V	For rench,	Wt. Each	
Each			ins.	lbs.	Each
F9396G	D4C5	(PJ6)	6	1/8	\$0.70
F9397G	D5C0	(PJ8)	8	1/4	.75
F9398G	D7C5	(PJ10)	10	1/2	1.15
F9399G	X1D05	(PJ14)	14	7/8	1.60
F9400G	X1 D45	(PJ18)	18	13/8	2.25
F9401G	X2D40	(PJ24)	24	21/8	3.60
4₽J36-G	X3D90		36	41/8	5.85
-‡PJ48−G	X6D20		48	67/8	9.35

Frames and Pin

			For	Wt.	
In which East		1	Vrench	, Each	
Each			ins.	lbs.	Each
-⊁PF6-G	D3C0		6	1/3	\$0.45
₩PF8-G	D4C0		8	1/4	.60
+PF10-G	D5C0		10	1/4	.75
F9391G	D5C5	(PF14)	14	1/2	.85
F9392G	D6C5	(PF18)	18	1/2	1.00
F9393G	X1D20	(PF24)	24	3/4	1.80
F9394G	X1D90	(PF36)	36	11/2	2.85
-₽PF48-G	X2D40		48	2	3.60

Nuts

For

Wt.

		W	rench,		
Each			ins.	OZS.	Each
F9404G	D1C5	(PN6)	6	1/2	\$0.25
F9405G	D1C5	(PN8)	8	1	.25
F9406G	D2C0	(PN10)	10	2	.30
F9407G	D3C0	(PN14)	14	4	.45
F9408G	D3C5	(PN18)	18	4	.55
F9409G	D4C5	(PN24)	24	8	.70
F9410G	D9C5	(PN36)	36	14	1.45

Frame Pins

Each		For Wrench ins.	Each
+FP6-G	D0C5	6	\$0.10
FP8-G	D0C5	8	.10
#FP10-G	D0C5	10	.10
₩FP14-G	D0C5	14	.10
₽ FP18-G	D0C5	18	.10
+FP24-G	D0C5	24	.10
4-FP36-G	D0C5	36	.10
 FP48−G	D0C5	48	.10

Fro	nt Sprin	gs With Pins	
Each		For Wrench, ins	Each
+FSP6-G	D0C6	6	\$0.10
+FSP8-G	D0C6	8	.10
+FSP10-G	D0C6	10	.10
-FSP14-G	D0C6	14	.10
₽FSP18-G	D0C9	18	.15
₩FSP24-G	D0C9	24	.15
₩FSP36-G	D0C9	38	.15
+FSP48-G	DOC9	48	.15

All above, loose

36 and 48 inch loose Items marked + not carried in stock. Can only be furnished by shipping direct from 'actory, F. O. B., Boston, Mass.

PIPE WRENCH REPAIRS



RIDGID-Front Jaw

Each			For Wrench inches	Weight Each, Il	Each
F9351G	DCC5	(RJ6)	6	1/4	\$0.97
F9352G	D7C0	(RJ8)	8	1/2	1.05
F9353G	X1D05	(RJ10)	10	3/4	1.55
F9354G	X1D45	(RJ14)	14	13/4	2.20
F9355G	X2D05	(RJ18)	18	21/4	3.05
F9356G	X3D15	(RJ24)	24	31/4	4.70

Heel Jaw and Pin

Each			For Wrench, inches	Weight Each, lb	Each
+RHJ6G	D3C5	(RHJ6)	6	1/A	\$0.55
F9345G	D4C0	(RHJ8)	8	1/8	.60
F9346G	D5C5	(RHJ10)	10	3/16	.80
F9347G	DEC5	(RHJ14)	14	1/4	1.00
F9348G	D7C0	(RHJ18)	18	8/8	1.05
F9349G	D7C5	(RHJ24)	24	1/2	1.10

Heel Jaw Pins

Each		For Wrench, inches	Weight Each, lb	Each
+RP6G	D0C5	6		\$0.10
+RP8G	D0C5	8	12	.10
+RP10G	D0C5	10		.10
+RP14G	D0C5	14		.10
₽RP18G	D0C5	18		.10
₩RP24G	D0C5	24		.10
+RP36G	D0C5	36		.10

Coil and Flat Springs

One each flat and coil springs.

Each		For Wrench, inches	Weight Each, lbs.	Each
+RCFS6G	D2C0	6		\$0.30
₽RCFS8G	D2C0	8	144	.30
+RCF510G	D2C0	10		.30
+RCFS14G	D3C0	14		.45
+RCFS18G	D5C0	18		.75
+RCFS24G	D5C5	24	-	.80
+RCFS36G	D6C0	36		.90
	N	uts		
		ch,	lbs	

Each Each (RN6) \$0.25 F9358G D1C5 16 F9359G D1C5 (RN8) 1/8 .25 .30 F9360G D2C0 (RN10) 10 3/16 .55 F9361G **D3C5** (RN14) F9362G **D3C5** (RN18) 18 1/2 .55

(RN24)

(RN36)

24

11/2

D5C0


X1 D00

F9363G

F9364G

PLIER-WRENCHES

PETERSON VISE



Straight Jaw Models

Double lever action. High grade alloy tool steel, hardened and tempered.

Each		Size in.	Jaw Thick- ness, in.	Jaw Adj. in.	▲Each
F7981G	X1D43 (7R)	7	7/16	11/8	\$2.15
	One in box.	Wτ.	box 3/4 1	b.	

F7982G X1D63 (10R) 10 5/8 11/4 2.45 One in box. Wt. box 11/4 lbs.



Involute Curved Jaw models

Made of heat treated alloy steel. Gives tooth contact on four points of nuts—increases tooth contact on round work. When used as clamp, pressure can be applied exactly where wanted.

Knurled jaw tips hold work at very tip with non-slip grip. Thin nose works in close quarters. Wire cutter even cuts smill bolts.

With Wire Cutter

Each	Jaw Jaw Size Thick- Adj. in. ness, in. in. ▲Each
F7988G	X1D67 (7WR) 7 1/4 15/8 \$2.50
	One in box. Wt. box 3/4 lb.
F7989G	X1D97 (10WR) 10 3/8 17/8 2.95
	One in box. Wt. box 11/4 lbs.
	Without Wire Cutters

One in box. Wt. box 3/4 lb.

1/4 17/8

F7987G X1D73 (10CR) 10 3/8 17/8 2.60 One in box. Wt. box 11/4 lbs.


F7986G X1D50 (7CR) 7

.75

1.50

PLIER-WRENCH DEAL

PETERSON VISE-GRIP



Simply press "easy-release" and jaws click open.

Three color display board 13 in, wide at base, $20\frac{1}{2}$ in, high, with pegboard hooks.

Consists of one each of the following:


	Size	
No.	in.	Type Jaw
7R	7	Straight
7CR	7	Curved
7WR	7	Curved, with Cutter
toR	10	Straight
10CR	10	Curved
10WR	10	Curved, with Cutter
The state of the s		

Per Deal (6DB) ▲Per Deal F7969G X9D93.....\$14.90

One in ctn. Wt. ctn. 10 lbs.

MERCHANDISE MANAGER'S SPECIAL PROMOTION

OUTBOARD MOTOR MAINTENCE KITS Challenger Imperial



Every tool required for repairing and adjusting outboard motors to peak efficiency plus an official Popular Mechanics' magazine "Outboard Motor Operation" manual.

Spark plug holding socket, with cushion insert, for inserting or removing plugs without dropping them in the water or burning fingers.

Includes following tools in plastic, waterproof, rool-up kit that folds to 11½x5x2 incheseach kit individually boxed—six kits in automatic merchandising carton:

3/8x7/16 inch Open end Wrench ½x9/16 inch Open end Wrench 5/8x¾ inch Open end Wrench 8 inch Phillips Screwdriver

8 inch Mechanics' Screwdriver 10 inch All-purpose Locking Pliers

6 inch Mechanics' Pliers

2 Ignition Files
7-Piece Spark Adjustment Tool
10-Piece Feeler Gauge
7-Piece Set Screwdriver set and Kit
Spark Plug Holding Socket
Shear Pin and Cotter Pin Pauch

(6195)

Per Kit F7980-G

X6D65

Per Kit

Jaws

ADJUSTABLE WRENCH



KEEN A KUTTER

Attractive sturdy metal display stand with double steel wire easel and brackets for holding wrenches. Width 10 inches. Height 13 inches. Display twelve wrenches. Wrenches have alloy steel frames and handles. Hardened jaws. Pelished heads. Silver finish web handle with hole for hanging.

Each

for hanging.
Red background with white trim.
Contains:

Oty.	No.	Length,	Cap.,
20,		stable Wrenc	
	90GK-K4	4	1/2

	Adjust	able Wrenc	hes	
2 3 2 2	F7890GK-K4 F7891GK-K6 F7892GK-K8 F7893GK-K10 F7894FK-K12	4 6 8 10 12 For	1/2 3/4 15/16 11/8 17/16	\$2.50 2.50 2.95 3.75 5.50
	W	/rench		
Qt	y. No.	No. Jaws		Each
1 1 1 1 1	F9453G-914J F9258G-916J F9259G-918J F9260G-9110J F9261G-9112J	K4 K6 K8 K10 K12		44 56 72
1 1 1 1 1 1	F9454G-914K F9262G-916K F9263G-918K F9264G-9110K F9265G-9112K	Knurls K4 K6 K8 K10 K12		18
1 1 1 1 1 1	F9455G-914P F9266G-916P F9267G-918P F9268G-9110P F9269G-9112P	K4 K6 K8 K10 K12		
1 1 1 1	F9456G-9145 F9270G-916S F9271G-918S F9272G-9110S F9273G-9112S	K4 K6 K8 K10		07 07 07

Per Display		Per Display
F7888GK	X27D77	.\$41.65
Wrenches	packed in individual boxes, parts in envelopes.	extra

Complete display in ctn. Wt. ctn. 8 lbs.

REPAIRS FOR ADJUSTABLE WRENCHES







Knurls

Pins

DIAMOND	EDGE.	KEEN	KUTTER	AND	UTICA
DIAMOND	LDUL,	LIFELL	MOITEM	MIL	01107

		Jaws					Knurls		
			For					For	
Each			Wrench	ins. Each	Each			Wrench ins	s. Each
F9453G	(914J)	D3C0	4	\$0.45	F9454G	(914K)	D1C2	4	\$0.25
F9258G	(916J)	D3C0	6.	.45	F9262G	(916K)	D1C2	6	.25
F9259G	(918J)	D3C7	8	.60	F9263G	(918K)	D1C4	8	.30
F9260G	(9110J)	D4C8	10	.75	F9264G	(9110K)	D1C5	10	.30
F9261G	(9112J)	D7C2	12	1.10	F9265G	(9112K)	D2C5	12	.50
				Pi	ns				
Each F9455G F9266G F9267G	(914P) (916P) (918P)	D0C5 D0C5 D0C5	For Wrench 4 6 8	ins. Each \$0.10	Each F9268G F9269G	(9110P) (9112P)	D0C5 D1C0	For Wrench ins. 10 12	Each .10 .20
1				Spr	ings				
Each F9456G F9271G	(914S) (918S)	D0C4 D0C4	For Wrench 4 8	ins. Each \$0.08 .08	F9273G	(9112 S)	D0C4	For Wrench ins. 12	Each .08
				CDECT	VOLOY				

CRESTOLOY

Pins and Springs for AC and AT Style Wrenches

			For	A				For	A
Each			Wrench	ins. Each	Each			Wrench	ins. Each
F9302G	(AC14J)	D3C3	4	\$0.50	F9316G	(AC14PS)	D0C4	4	\$0.06
F9303G	(AC16J)	D3C6	6		F9317G	(AC16PS)	D0C4	6	.06
F9304G	(AC18J)	D4C5	8	.68	F9318G	(AC18PS)	DOC4	8	.06
F9305G	(AC110J)	D5C7	10	.86	F9319G	(AC110PS)	DOC4	10	.06
F9306G	(AC112J)	D8C4	12	1.26	F 9320G	(AC112PS) (AC115PS)	D1C1	12 15	.17
F9307G	(AC115J)	X1D25	15	1.88	F9329G	(AC118PS)	D1C3	18	.20

Knurls-For AC and AT Style Wrenches

			For		Each			For	
Each			Wrench ins	s. Each				Wrench ins.	Each
F9309G	(AC14K)	D1C3	4	\$0.20	F9312G	(AC110K)	D1C9	10	.30
F9310G	(AC16K)	D1C3	6	.20	F9313G	(AC112K)	D2C9	12	.45
	(AC18K)		8			(AC115K)			.60

For Type "A" CRESCENT Wrenches

	Jaws				Pins and Springs				
			For					For	A
Each			Wrench is	ns. Each	Each			Wrench in	s. Each
F9275G	(A16J)	D2C9	- 6	\$0.45	F9288G	(A14PS)	D0C4	4	\$0.09
F9276G	(A18J)	D3C3	8	.50	F9289G	(A16PS)	D0C4	6	.08
F9277G	(A110J)	D4C7	10	.70	F9290G	(A18PS)	D0C4	8	.08
F9278G	(A112J)	D6C9	12	1.05	F9291G	(A110PS)	D0C4	10	.08
	,		THE PERSON OF THE PERSON		F9292G	(A112PS)	D1C1	12	.22
F9279G	(A115J)	D9C6	15	1.44	F9293G	(A115PS)	D1C1	15	.22
F9280G	(A118J)	X1D37	18	2.06	F9294G	(A118PS)	D1C3	18	.22

Knurls-For Type "A" Wrenches

No. 53 Table			For		Each			For	
Each			Wrench is					Wrench ins.	Each
F9281G	(A14K)	D102	1	90 00	F9284G	(A110K) (A112K)	D1C9	10	.30
A LANCE OF THE PARTY OF THE PAR				DU . 22	F9285G	(A112K)	D2C9	12	.45
F9282G	(A16K)	D1C3	6	.22	F9286G	(A115K)	D3C9	15	.60
F9283G	(A18K)	D1C7	8	.24	F9287G	(A118K)	D4C5	18	.68
				All abov	e, Loose				

ADJUSTABLE WRENCHES



KEEN KUTTER

Thin Pattern

Alloy steel frame and handle. Hardened jaws. Polished head. Silver finish web handle with hole for hanging.

Single Head

Each F7890GK	(K4)	X1 D67	Length, ins.	Capacity, ins.	Wt. Box, lbs.	Each \$2.50
F7891GK	(K6) ·	X1 D67	6	3/4	1/4	2.50
F7892GK	(K 8)	X1 D97	8	15/16	3/4	2.95
F7893GK	(K10)	X2D50	10	11/8	1	3.75
F7894GK	(K12)	X3D67≠		17/6 n box	13/4	5.50



Thin Jaw Type

Forged from alloy steel. Nickel plated finish

Each				in a Carton	Cap., ins.	ctn. lbs.	Each
F3366G	(F1)	X1D46★	6	4	3/4	1	\$2.20
F3367G	(F2)	X1D66★	8	4	15/16	2	2.50
F3368G	(F3)	X2D13	10	6	11/8	$5\frac{1}{2}$	3.20
F3369G	(F4)	X3D15	12	2	15/16	3	4.75

ADJUSTABLE WRENCHES

CRESCENT



CRESTOLOY

Chromium Plated Single End

A newly developed steel by the makers of Crescent wrenches will withstand a strain of over twice that required to break a regular Crescent wrench; yet they are one third thinner and much lighter. Handle dull satin finish, heads polished and buffed.

			1	Thickness of Head				
Each F7877G (AC14)	X1D67	Lgth., ins.	Cap., ins.	Thickest Point, ins.	Tip of Jaw, in.	Wt. Box, lbs.	▲ Each \$2.50	
F7878G (AC16)	X1D69★	6	3/4	13/32	7/82	1/4	2.55	
F7879G (AC18)	X1 D 97★	8	15/16	15/32	8/32	1/2	2.95	
F7880G (AC110)	X2D51 ★	10	11/8	%16	13/32	7/8	3.75	
F7881G (AC112)	X3D63 ★	12	15/16	24/32	15/32	15/8	5.52	
F7882G (AC115)	X5D53	15	111/16	15/16	19/32	31/4	8.30	
F7883G (AC118)	X9D00	18	21/16	11/8	11/16	51/4	13.50	
F7884G (AC124)	X15D07		2½6 in box	113/32	7/8	9	22.60	



ENGINEERS' ADJUSTABLE Single End-Thin Jaw

Drop forged steel handles. Hardened tool steel jaws, 4 inches to 12 inches. Side of jaws polished, balance black oil finish.

Each F7871G (AT16)	Length, inches X1D33★ 6	Capacity inches	Wt. Box lbs.	▲ Each \$1.90
F7872G (AT18)	X1D60★ 8	15/16	3/4	2.25
F7873G (AT110)	X1D96★ 10	11/8	11/4	2.75
F7874G (AT112)	X2D97★ 12	15/16	2	4.20
F7875G (AT115)	X4D65 15 One i	111/16 n box	43/8	6.60

WRENCH SET

VLCHEK Open End



Drop forged new "Parabolic" carbon steel, milled openings. Tempered, natural finish. Each set securely held in all-metal sidehinged positive locking container. 5 piece set, 5/16 to 3/4 inch opening. ▲Per Set

....\$1.80

F8054G (X2163) X1D20★..... Loose. Wt. set 2 lbs.

Per Set

MERCHANDISE MANAGER'S SPECIAL PROMOTION

ADJUSTABLE WRENCHES

BILLINGS & SPENCER



Ruggedly constructed -only three parts. Capable of precise adjustment

Carbon steel one-piece handle and front jaw. Carbon steel movable jaw. Long nut and sleeve. Natural rust-proof finish, with disced jaws.

Each			Lgth.,	Jaws Open, ins.	Wt. Box, 1bs.	A Each
F7849G F7849G F7850G	X3D75 X4D97 X6D31	(BS90/12) (BS90/15) (BS90/18)	12 15 18	21/4 3 4	17 26 34½	\$5.62 7.46 9.46
		Six in pk	œ.			

TRUECRAFT



Made in Japan

Alloy Steel

Exceeds tensile strength required for normal duty.

Fully polished on all surfaces except inside of handles.

				-	
Each	Pri	ce	In.	Box, Lbs.	Each
F7867C	.90 (F6)	6	2	\$1.39
F7870G	1.10 (F8)	8	21/4	1.69
F7868G	1.50 (F10)	10	5	2.25
F7869G	2.05 (F12)	12	3	3.10

One In A Box

WRENCH SETS

BARCALO

Combination Box and Open End



123/4x111/8x61/2 inches. Color fast vacuum-formed plastic reinforced display board.

Four sets of 6 wrenches to fit 31 types of nuts and bolts in handy pocket pack.

Handy storage compartment in back holds supply of extra wrench sets.

Drop forged from alloy steel, chrome plated highly polished end and panels. Smooth finish sides.

		Each set consists of one each	
	Length, inches	Opening inches Open and box ends	
	4½ 5 5% 6¼ 7	35 76 74	
	614 7 85/8	9/6 5/6 3/4	
		Counter display (No charge)	
Per Set		(CD1346P)	Per Set
F8030G	X14D67	One set in box. Wt. box 61/4 fbs.	\$22.00
- 1		One set in Dux, we, nox 074 ms.	

WRENCII DISPLAYS BILLINGS & SPENCER LIFE-TIME



Magic Clerk

Forged from selected alloy steel. Openings are clean and accurately machined. Handles are slim and round edged. Scientifically heat treated. Heads polished. Finished with an attractive and practical over all chrome plate.

An eye catcher, with sales appeal. Attractive plywood counter display, finished in rich royal blue. Exclusive permanent magnetic device for holding wrenches, guaranteed to hold its power for a life time. Spaces properly marked for each wrench. Wire supports at bottom for box wrenches. Partitioned pockets on back for refill stock. Wrenches can be removed for inspection. Easy to set up.

Length 18 inches. Depth 8 inches. Height 24 inches

Contents:

Engineers

Quantity		Openings, ins.	Length, ins.	Each
4	F8303G-L1020	14 & 5/6	31/2	\$0.64
4	F8323G-L1723	3/8 & 1/6	434	.64
4	F8325G-L1725B	1/2 & 9/6	6	.74
4	F8327G-L1729	5/8 & 3/4	8	1.04
4	F8329G-L1731B	13/16 & 7/8	91/2	1.46
3	F8308G-L1033C	15/16 & 1	91/2	1.72
	45° Box			
4	F8331G-L8723	3/8 & 7/18	81/2	.80
4	F8332G-L8725B	1/2 & 9/16	9	.90
4	F8333G-L8729	5/8 & 3/4	11	1.12
4	F8334G-L8731B	13/16 & 7/8	125%	. 93
3	F8330G-L8033C	15/16 & 1	151/2	1.78
	Combinati	on		
4	F8310G-L1161	7/16	53/8	.78
4	F8311G-L1162	1/2	6	.92
4	F8312G-L1163	9/16	63/4	.98
4	F8313G-L1164	5/8	75/8	1.08
4	F8314G-L1165	11/16	81/2	1.14
4	F8315G-L1166	3/4	91/2	1.30

66 Wrenches-3 Popular Styles


Each		A Each
FX-EBC66-G	X50D39	\$75.58
	One in ctn. Wt. ctn. 36 lbs.	

WRENCHES

NEW BRITAIN MACHINE CO.

None Better

Chrome Alloy-Polished and Lacquered





BOX END WRENCHES

45° Long

Each			Milled Opening inches	For U. S. S. Nut; Size Bolt, inch	For Hex Head Cap screw inch	For S. A. E. Std. Screw & Nut inch	Length inches	Weight Box, 1bs.	Each
F8381G	D6C0	(NB8725B)	1/2 & 1/6	1/4 &	5/6 & 3/8	16 & 1/4	85%	21/4	# .90
F8386G F8377G	D9C7 X1D19	(NB8731B) (NB8033C)		& 1/2	% & % & %	& 1/6 5/8 & 1/6	115% 1414	61/8 81/6	1.46 1.78
					15° Long				
F8371G	D5C6	(NB7723)	3/8 & 1/6	&	& 1/4	& 1/2	73/4	11/2	.84
F8372G	D6C0	(NB7725B)	12 & 1/6	1/4 &	5/6 ₺ 3/8	% de 3/8	8%	234	.90
					15° Short				
F8368G	D5C9	(NB6725B)	36 & 96	1/2 &	% & %	% & %	41/8	11/6	.88
					Six in a box				

COMBINATION WRENCHES

Each			Milled Opening inches	For U. S. S. Nut; Size Bolt, inch	For Hex Head Cap Screw inch	For S. A. E. Std. Screw & Nut inch	Length inches	Weight Each, ozs.	Each
F8351G	X1 D01	(NB1167A)	13/16 & 13/16		9/16	3240	103/8	9	# 1.52
F8352G	X1D28	(NB1168)	15/16 & 15/16			5/8	11	13	1.92
				Si	x in box				

WRENCHES BILLINGS & SPENCER LIFE-TIME

Assured proper design, strength, lightness and long life.

Forged from selected alloy steel. Openings are clean and accurately machined. Handles are slim and round edged. Scientifically heat treated. Heads polished. Finished with an attractive and practical over all chrome plate.

Engineers

Each	Openings Milled (Nominal), inches	For U. S. Std. Nuts; Size Bolts, inches	For Hex. IId. Cap Screws; Dia. Screws, inches	For S. A. E. Std. Nuts; Size Bolts, inches	For Amer, Std Reg, Nuts; Size Bolts, inches	Length (App.), inches	Thickness Head, inches	Weight, Box, lbs.	▲ Each
F8305G D6C8 (I	L1027) 19/32 & 11/16	5/16 & 3/8	- & -	- & -	- & -	7	%2	11/2	# 1.02
F8328G X1D07 (L	L1731A) 34 & 3/8	- & 1/2	1/2 & 5/8	1/2 & 1/6	7/6 & 9/6	$9\frac{1}{2}$	3/8	31/2	1.60
F8307G D9C1 (L	_1031) ²⁵ / ₃₂ & 7/ ₈	76 & 1/2	- & 1/6	- & 1/6	- & %	91/2	23 64	6	1.36
F8309G X1D27 (L	-1034) ½ & 1½	1/2 & 5/8		% & ¾ a box 5° Box	% &	11	13/12	9	1.90
Each	Opening, inches	For U. S. S. Amer. Std. Heavy Nut, Size Bolt, in.	For Amer. Stand. Hex. Cap Screw, inches	For S. A. E. Amer. Std. Light Nut Size Bolt, in.	For Amer. Std. Regular Nut Size Bolt, in.	Length Approx., inches	Weight Box, lbs.	No. in Box	▲ Each
F8333G D7C9 (L	8729) 5/8 & 3/4	- & -	7/16 & 1/2	7/6 & 1/2	3/8 & 1/6	11	31/2	6	# 1.18

Six in a box

WRENCH DISPLAY ASSORTMENTS


INDESTRO SELECT STEEL

Drop-Forged-Scientifically Heat-Treated

Clean, Accurate Broaching-Brightly Plated-Polished Heads

Servatool displays include metal hanger with pricing strips—can be mounted on perforated board at hanger ends or hung anywhere with hanger brackets furnished.

OPEN END WRENCHES




Servatool 21-Piece Assortment

		Conter	Its:	
Otv.	N	0.	Opening, in.	▲ Each
3	F8130G	(P20)	1/4 & 5/16	\$0.53
3	F8131G	(P723)	3/8 & 7/16	.61
3	F8132G	(P725B)	1/2 & 9/16	.72
3	F8133G	(P27)	19/32 & 11/16	.83
3	F8134G	(P729)	5/8 & 3/4	.95
3	F8135G	(P731B)	13/16 & 7/8	1.19
3	F8136G	(P33C)	15/16 & 1	1.47

Per Display Per Display FX-5304-G X13 D61..... One Display in box. Wt. box 7 lbs.

BOX WRENCHES



Servatool 14-Piece Assortment


	Conter	its:	
Oty.	No.	Opening, in.	▲ Each
3	F8293G (911)	3/8 & 7/6	\$0.76
3	F8294G (912)	1/2 & 9/16	.86
2	F8295G (913)	5/8 & 11/16	.99
2	F8296G (914)	3/4 & 25/32	1.15
2	F8297G (915)	13/16 & 7/8	1.37
2	F8298G (916)	15/16 & 1	1.82

FX-5305-G X10D91... \$16.78

Per Display

One display in box. Wt. box 10 lbs.

COMBINATION WRENCHES



Servatoo! 18-Piece Assortment

Contents:

No.	Opening, in.	Each
F7319G (1071)	3/8	\$0.64
F7320G (1072)	7/16	.69
F7321G (1073)	1/2	.73
F7322G (1074)	9/16	.84
F7323G (1075)	5/8	.97
F7324G (1076)	11/16	1.11
	F7319G (1071) F7320G (1072) F7321G (1073) F7322G (1074) F7323G (1075)	F7319G (1071)

Per Display Per Display FX-5312-G X10D58 \$16.26

One display in box. Wt. box 5 lbs.

Servatool 10-Piece Assortment

Contents:

Per Display


Per Display

Qty.	No.	Opening, in.	Each
2	F7325G (1077)	3/4	\$1.25
2	F7326G (1078)	13/16	1.52
2	F7327G (1079)	7/8	1.67
2	F7328G (1080)	15/16	1.84
2	F7329G (1081)	1	2.06

FX-5314-G X11D70\$18.01 One display in box. Wt. box 5 lbs.

OPEN END, BOX AND

COMBINATION WRENCHES



For use with counter type Servatool salesmaker or individually on walls, posts or islands.

All wood construction, size 13x31 ins.; finished in yellow and red.

Contents:

Open End Wrenches

Qty.	No.	Opening, in.	Each
3	F8131G (P723)	3/8 & 7/15	\$0.61
3	F8132G (P725B)	1/2 & 1/6	.72
3-	F8133G (P27)	19/32 & 11/16	.83
3	F8134G (P729)	5/8 & 3/4	.95
3	F8135G (P731B)	18/16 & 7/8	1.19
3	F8136G (P33C)	15/16 & 1	1.47
	Combination		

Combination Wrenches

3

F7320G (1072)	7/16	.69
F7321G (1073)	1/2	.73
F7322G (1074)	9/16	.84
F7323G (1075)	5/8	.97
F7324G (1076)	11/16	1.11
F7325G (1077)	3/4	1.25
F7326G (1078)	13/16	1.52

45° Box End Wrenches

3	F8293G (911)	3/8 & 7/16	.76
3	F8294G (912)	3/2 & 9/6	.86
3	F8295G (913)	5/8 & 11/16	.99
}	F8296G (914)	3/4 & 25/12	1.15
	F8297G (915)	13/16 & 7/8	1.37
	F8298G (916)	15/16 & 1	1.82

Per Display Per Display Per Display 4-5046W-G X40D11..... \$62.71

One display in ctn. Wt. ctn. 27 lbs.


Items marked - not carried in stock. Can only be furnished by shipping direct from factory, F. O. B., Chicago, III.

WRENCH SETS

INDESTRO SELECT STEEL

Drop-Forged—Scientifically Heat-Treated
Clean, Accurate Broaching—Brightly Plated—Polished Heads








5 Piece Set Range 5/16 to 3/4 in.

 Per Set
 Per Set

 F8059G
 (0930-5W)
 X1D37
 \$2.15

 Six sets in box. Wt. box 5 ½ lbs.





6 Piece Set

IGNITION




4 Piece Set

15° and 60° Openings

Wrench Sizes 1/2 and 1/4, 13/4 and 15/4, 5/6 and 9/2, 11/2 and 3/8 in. Mounted on colorful merchandising card.

COMBINATION



5 Piece Set

Range 3/16 to 3/4 in.

Twelve sets in box. Wt. box 9 lbs.



6 Piece Set

Range 1/6 to 1/8 in.

UTILITY



8 Piece Set

For ignition systems, carburetors, radio, television and anywhere the application of small tools is required.

Contains:

- 4-Open End Wrenches, one each 1/4 and 1/32, 11/42 and 11/44, 5/16 and 1/32, 11/32 and 3/8 in.
- 1-Midget Plier
- 1—Shockproof Midget Screw Driver
- 1-Tungsten Ignition File
- 1—Swedish Steel Feeler Gauge with Blades .012, .015, .018, .020 and 025. In attractive enameled box.


One set in box. Wt. box 1 lb.

WRENCH SETS

INDESTRO SELECT STEEL


Drop-Forged—Scientifically Heat-Treated
Clean, Accurate Broaching—Brightly Plated—Polished Heads

Klip-Tite sets have utility wall brackets designed so wrenches can be hung or removed speedily. Two holes in red enameled bracket for easy attachment to wall.



5 Piece Klip-Tite Set

12 Point Opening Range 3/8 to 7/8 in.



6 Piece Klip-Tite Set

12 Point Opening Range 3/8 to 1 in.

45° SHORT BOX




3 Piece Set

12 Point Opening Range 3/8 to 11/6 in

COMBINATION





5 Piece Klip-Tite Set


Range 1/16 to 11/16 in.

Per Set Per Set

F8032G (01070-05W) X2D27......\$3.54

Six sets in box. Wt. box 7½ lbs.






6 Piece Klip-Tite Set

Range 1/16 to 3/4 in.

Six sets in box. Wt. box 18 lbs.



14 Piece Set

In colorful, modern, reinforced vinyl plastic tool roll with clear plastic pockets.

Per Set		Per Set
F8067G	(1068)	X13D04\$20.38
		One set in a boy. Wt. boy 61/ Iba

WRENCHES

INDESTRO SELECT STEEL

Drop-Forged—Scientifically Heat-Treated, Clean
Accurate Broaching—Brightly Plated—Polished Heads

OPEN END



Each			Opening, in.	Box 1bs.	▲Each
F8130G	(P20)	D3C6	1/4 & 5/16	1/4	\$0.55
F8131G	(P723)	D4C1	3/8 & 7/16	1/2	.64
F8132G	(P725B)	D4C8	1/2 & 9/16	1	.75
F8133G	(P27)	D5C6	19/32 & 11/16	11/2	.86
F8134G	(P729)	D6C4	5/8 & 3/4	2	1.00
F8135G	(P31B)	D8C4	13/16 & 7/8	3	1.31
F8136G	(P33C)	X1 D01	15/16 & 1	43/4	1.58

Six in box


BOX



				THE PARTY OF THE P	
Each			Opening, in.	Wt. Box Ibs.	▲Each
F8293G	(911)	D5C1	3/8 & 7/16	1	\$0.79
F8294G	(912)	D5C8	1/2 & 9/10	11/2	.90
F8295G	(913)	D6C7	5/8 & 11/16	2	1.04
F8296G	(914)	D7C7	3/4 & 25/32	23/4	1.20
F8297G	(915)	D9C2	13/16 & 7/8	33/4	1.44
F8298G	(916)	X1 D23	15/16 & 1	5	1.93

Six in Box

COMBINATION



Each			Opening, in.	Wt. Box Ibs.	Each
F7319G	(1071)	D4C4	3/8	1/2	\$0.69
F7320G	(1072)	D4C7	7/16	1/2	.73
F7321G	(1073)	D5C0	1/2	3/4	.77
F7322G	(1074)	D5C6	9/16	11/4	.88
F7323G	(1075)	D6C6	5/8	11/2	1.02
F7324G	(1076)	D7C5	11/16	2	1.17
F7325G	(1077)	D8C4	3/4	21/2	1.31
F7326G	(1078)	X1 D01	13/10	3	1.58
F7327G	(1079)	X1D12	38	4	1.75
F7328G	(1080)	X1524	1.5	45%	1.94
F7329G	(1081)	X1 D39	D.	5	2.17

Six in box.

WRENCH AND TOOL SETS

INDESTRO



47 Piece Set

Contents:

1/2 in. Drive Sockets & Fittings

10-Sockets, range 1/16 to 1 in.

1—Reversible Ratchet

1-Swing Handle, 151/2 in.

1-Cross Bar, 9 in.

1/4 in. Drive Sockets & Fittings

In transparent plastic box

8-Sockets, range 1/2 to 3/8 in.

1—Extension 3¾ in.

1-L Handle, 4 in.

1-Spinner Handle, 61/2 in.

Open End Wrenches

5 Pieces-10 sizes range 1/16 to 3/4 in.

45° Long Box End Wrenches

5 Pieces-10 sizes range 3/2 to 3/2 in.

Allen Type Wrenches

7 Pieces set—range 1/4 to 1/4 in.

1-Ignition and Hobbyist Set

3-Midget End Wrenches

1-Ignition File

1-Feeler Gauge

1—Pocket Klip Screw Driver Red Steel Box 19x71/2x61/2 in.

Per Set		Per Set
FX-80228A-G	X22 D50	\$35.25

One set in ctn. Wt. ctn. 18 lbs.

MERCHANDISE MANAGER'S SPECIAL PROMOTION

SOCKET WRENCH SOCKETS NEW BRITAIN MACHINE CO'S, "NONE BETTER"

Chrome Alley-Polished and Lacquered



HARGRAVE

1/2-inch Square Drive Straight Thin Wall 12-Point-Double Hex

Extra Deep

Height Over All 31/2 Inches

Each			Size in.	Wt.	A Each
F8503G	X1D27	(TD34)	11/18	412	1.90
F8504G	X1D27	(TD36)	11/8	5	1.90

Five in ctn.

(T1219) 19/3 1 F8479G D4C1

SOCKET WRENCH BRACE ADAPTERS HARGRAVE

For Socket with 1/9-inch Drive

Can be used in a brace with any type 1/2-inch drive socket.

Forged steel, heat treated. Nickel plated finish

(148)

Each A Each F8277G X1D88 \$2.82

Three in box. Wt. box 9 ozs.

SOCKET WRENCH SETS



12 Piece Set-1/2 inch Square Drive

Straight Thin Wall Sockets

Chrome alloy, triple chrome plate. Black damaskené finished steel box 15x234x11/2 inches.

Consists of:

10—12 point sockets, one each 1/6, 1/2, 1/6, 1/6, 1/8, 1/4, 11/6, 1/8 and 15/6 inch.


1-Flexible handle 15 inches long.

1--Cross bar 8 inches long.

(6012)

A Per Set F8039G X8D00 \$12.00

One set in box. Wt. box 5 lbs.



SOCKETS AND DRIVE PARTS DISPLAYS

NEW BRITAIN MACHINE CO.

"NONE BETTER"

Chreme Alloy-Polished and Lacquered

Display Ponel Sturdy, light-weight Masonite panel 1 x 2 feet. Large enough for attention value and handy enough to permit extreme flexibility of arrangements. Rich green background sets off the lustre of the tools. White space above each tool for prices.

Contains 38 sockets and drive tools as below:

PERM	SOURCE THE SHALL		
Quan	tity : No.	Description Lis	t Each
12	F8415G-S24	5-inch Socket Extension	\$1.26
2	F8416G-S25	10-inch Socket Extension	1.52
.2	F8417G-S30	8-inch Cross Bar	.38
2	F8419G-S41	Reversible Ratchet	6.32
2	F8421G-S53	15-inch Flex Handle	3.58
2	F8422G-S60	Universal Joint	2.14
2	F8423G-S70	Slide Tee Handle	
1	T816	1/2-inch 8-Point Socket	.80
1	T818	%-inch 8-Point Socket	,80
1	T820	%-inch 8-Point Socket	.80
2	F8476G-T1214	16-inch 12-Point Socket	.58
2	F8477G-T1216	1/2-inch 12-Point Socket	.58
. 2	F8478G-T1218	%-inch 12-Point Socket	.62
2	F8479G-T1219	13%inch 12-Point Socket	.62
2	F8480G-T1220	5%-inch 12-Point Socket	.62
2	F8482G-T1222	1/6-inch 12-Point Socket	.70
2	F84830-T1224	3/4-inch 12-Point Socket	.78
2	F8485G-T1226	13/6-incn 12-Point Socket	.82
2	F8486G-T1228	1/4-inch 12-Point Socket	.90
2	F8487G-T1230	15/6-inch 12-Point Socket	.94
2	F8489G-T1232	1-inch 12-Point Socket	.98
	1/1	-Inch Square Drive	
Each			Each
2-X-W	IB6263-G X	34D58	51.88

One in shipping container. Wt. container 23 lbs.

BRACE SOCKET WRENCHES



HARGRAVE Square Opening

For U. S. Standard nut sizes

Forged steel, heat treated. Shoulder prevents nut working far up into the wrench. Open shank prevents clogging and enable use where a brace will not go. Size Weight

Opening, Each inch 11/10 11.92 F8292G X1D28 (1560)

Six in box


SOCKET WRENCH DISPLAY ASSORTMENTS

INDESTRO CHROME ALLOY

Chrome Alloy Steel-Scientifically Heat-Treated-Rich Chrome Finish Thin Wall, Hot Broached, Four-Way Lock-On Sockets

Servatool displays include metal hanger with pricing strips—can be mounted on perforated board at hanger ends or hung anywhere with hanger brackets furnished.

3/8 IN. SQUARE DRIVE



Servatool 43 Piece Assortment

Size 10x17 inches.

Contains:

			Contains.	Size		
O	N	o.	Item	in.	Each	16
Qt						1
2 2 1	F8392G			3	\$0.96	
2	F8393G			6	1.28	
2	F8394G	(2735)		12	1.55	
1		(2763)		8		
2	F8396G	(2781)		0	0.07	
	201010	(0000)	Handle	9	2.67	
2	F8401G		Speeder	161/2	$\frac{2.10}{2.29}$	
1	F8397G			113/16	2.29	
2	F8414G	(2775)	Reversible		- 0-	
			Ratchet	8	5.65	
			Point Sockets			
					- 21	
2	F8	431G (2712)	3/8 in.	. 54	- 10
						El:
		12	Point Sockets			
9	FS	432G (7/16	.54	
2 2 2 2 2 2 2 2 2			2716)	1/2	.54	
2			2718)	97.	.54	0
9			2720)	5%	.54	Qty.
2			2722)	5/8 11/16 3/4	.61	2 F
2			2124)	3/16	.63	2 F
2		437G (2726)	13/	.77	2 F
2				13/16		2 F2 2 F3 2 F3 2 F3
2	F8	439G ((2728)	1/8	.88	
						1 F
	6 Pc	int Ur	niversal Joint S	ockets		
1	F8	449G ((2714UV)	7/16	2.31	Otv
1	F8	450G	2716UV)	1/2	2.31	200
î	F8	451G	(2718UV)	9/16	2.31	5
1			(2720UV)	5/8	2.31	2
	7,2			, 0		5
		12 D-	int Doon Cooks	4		Oty. 2 2 2 2 2 2 2 1 1
	400		int Deep Socke	W	- 1	2
1			(2742)	7/16	.79	2
1			(2743)	1/2	.79	2
1 1 1			(2744)	16	.86	2
1			(2745)	%	.91	2
1			(2746)	11/16	.99	1
			(2747)	3/4	1.04	1
1	F8	3448G	(2748)	13/16	1.24	1
						1 1

FX-5310-G X40 D91.....\$59.07 One Asst. in box. Wt. box 10 lbs.

Per Asst.

Per Asst.

1/2 IN. SQUARE DRIVE



Servatool 14-Piece Socket Assortment


Size 81/2x5 inches

Contents:

Qty.	No.	Size in.	Each
2	F8495G (3020)	5/8	\$1.28
$\frac{2}{2}$	F8496G (3022)	11/16	1.28
2	F8497G (3024)	3/4	1.28
$\frac{2}{2}$	F8499G (3026)	13/16	1.44
2	F8500G (3028)	1/8	1.58
2	F8501G (3030)	15/16	1.71
2	F8502G (3032)	1	1.78
Per D	isplay	Pe	r Display

FX-5320-G X14D20......\$20.63

One display in box. Wt. box 7 lbs.



Servatool 34-Piece Assortment

2

2

2

2 2 2

Size 12x22 in.


		Co	ontent:	Size	
0	tv. 1	Vo.	Item	in.	Each
	F8415G		Exten i n	51/2	\$1.31
2	F8416G	(3211)	Extension	10	1.62
2	F8421G	(32221)	Swing Handle	151/2	4.06
2	F8426G	(3208)	Long Speeder	19	2.17
2	F8419G	(3275)	Reveri le Rate	chet	6.59
	F8422G		Universal J int		2.23

No.	Siza, in.	Each
F8476G (121-		\$0.59
F8477G (121)	6) 16	.59
F8478G (121)		.63
F8480G (1220)) 3/8	.63
F8482G (122)	2) 11/16	.74
F8483G (122-	4) 3/4	.81
F8485G (1220	5) 13 ₁₆ 8) 7 ₈ 0) 15 ₁₆	.86
F8486G (122)	8) 7/8	.94
F8487G (1230)) 15/ ₁₆	.96
F8489G (123)	2) 1	1.04
F8490G (123-	4) $1\frac{1}{16}$	1.14
F8491G (1230		1.24
F8492G (1246	0) 11/4	1.28
Display	Per	- Display

FX-5306-G X36D76.... One display in box. Wt. box 22 lbs.

1/2 IN. SQUARE DRIVE

46-Piece Assortment Display Board



For use with counter type Serva-Tool salesmaker or individually on walls,

posts or islands.

All wood construction, size 13x31 in., finished in vellow and red.

Complete with Sockets, Handles and Fittings as follows:

Hexagon Sockets 12 Point

ty.	No.	Size in.	Each
	F8476G (1214)	7/16	\$0.59
	F8477G (1216)	1/2	.59
	F8478G (1218)	9/16	.63
	F8480G (1220)	5/8	.63
	F8482G (1222)	11/16	.74
	F8483G (1224)	3/4	.81
	F8485G (1226)	13/16	.86
	F8486G (1228)	7/8	.94
	F8487G (1230)	15/16	.96
	F8489G (1232)	1	1.04
	F8490G (1234)	11/16	1.14
	F8491G (1236)	11/8	1.24
	F8492G (1240)	11/4	1.28

Square Sockets 8 Point

-			
	(1216S)	1/2	.841/2
10	(1218S)	9/16	.841/2
	(1220S)	5/8	.841/2
	(1224S)	34	.99
	(1228S)	7/8	= 1.09

Handles and Fittings

				SIZE	
Q	ty. N	o.	Item	in.	Each
2	F8415G	(3216)	Extension	512	\$1.31
2	F8416G	(3211)	Extension	10	1.62
2	F8421G	(3222)	Swing Handle	1516	4.06
2	F8426G	(3208)	Speeder	19	2.17
2		(3201)	Reversible Ratchet	1013	6.59

Per Display Per Display +5048W-G X42D47.....\$61.08

One display in ctn. Wt. ctn. 29 lbs.

INDESTRO CHROME ALLOY

Chrome Alloy Steel—Scientifically Heat-Treated—Rich Chrome Finish
Thin Wall, Hot Broached, Four-Way Lock-On Sockets

1/4 IN. SQUARE DRIVE



11 Piece Set

Contents:

6-Hexagon 6 point sockets, one each 1/4, 1/32, 1/6, 11/32, 1/8, 1/6 in.


3-Square 8 Point sockets, one each 1/4, 5/16, 3/8 in.

1-Swing Head Handle, 6 in.

1-Cross bar 4 in.

Red steel box 67/8 x 2 x 1 in.

Per Set		Per Set
F8040G	(7600)	X3D52\$5.50
		One set in box. Wt. box 1 lb.



14 Piece Set

Contents:

8—Hexagon 6 Point Sockets, one each 3/6, 1/32, 1/4, 9/32, 5/16, 11/32, 3/8, 1/6 in.

3-Square 8 Point Sockets, one each 1/4, 5/6, 3/8 in.

1—Reversible Ratchet


1-Extension 3 in.

1-Spinner Handle 6 in.

Red steel box 63/8 x 23/4 x 1 in.

Per Set		Per Set
F8046G	(7602)	X7D33\$11.46
		One set in box. Wt. box 2 lbs.

3/8 IN. SQUARE DRIVE



11 Piece Set

Contents:

1-Hexagon 6 Point Socket 3/8 in.

6-Hexagon 12 Point Sockets, one each 1/6, 1/2, 9/6, 5/8, 11/6, 3/4 in.

1-Reversible Ratchet

1-Socket Extension 6 in.

1—Swing Head Handle 9 in.

1-Cross Bar 51/2 in.

Red steel box 93/4 x 33/4 x 11/4 in.

Per Set		Per Set
F7972G	(7701)	X9D77\$15.28
		One set in box, Wt, box 3½ lbs.



15 Piece Set

Contents:

1-Hexagon 6 Point Socket 3/8 in.

6-Hexagon 12 Point Sockets, one each 1/16, 1/2, 9/16, 5/8. 11/16, 3/4 in.

2-Square 8 Point Sockets, one each 1/6, 1/2 in.

1-Extension 6 in.

1-Universal Icint

1-Cross Bar 51/2 in.

1-Swing Head Handle 9 in.

1-Speeder 16 in.

1-Reversible Ratchet

Red steel box 171/4 x 51/4 x 11/4 in.


Per Set		Per Set
F8047G (7702)	X14D93	. \$23.34

One set in box. Wt. box 6 lbs.

INDESTRO CHROME ALLOY

Chrome Alloy Steel-Scientifically Heat-Treated-Rich Chrome Finish Thin Wall, Hot Broached, Four-Way Lock-On Sockets

1/2 IN. SQUARE DRIVE



12 Piece Set

Contents:


10—Hexagon 12 Print Sockets, one each 7/16, 1/2, 9/16, 5/8, 11/16, 3/4,

13/6. 78, 15/6, 1 in. Swing Head Handle 111/4 in.

1-Cross Bar, 9 in.

Red steel box 121/4 x 23/4 x 2 in.

Per Set Per Set F8049G (7803) X8 D00..... ... \$12.50 One set in box. Wt. box 5 lbs.



17 Piece Set

Contents:

13—Hexagon 12 Point Sockets, one each, 1/6, 1/2, 1/6, 11/2, 5/8, 11/6, 3/4, 11/6, 1/8, 11/6, 1/8 in.

1—Extension 51/2 in.

1—Swing Head Handle 151/2 in.

Cross Bar 9 in.

Reversible Ratchet

Red steel box 161/4 x 23/4 x 21/8 in.

Per Set			Per Set
F8048G	(7805)	X16D20	525.22
		One set in box Wt bee 814 Be	



18 Piece Set

Contents:

13—Hexagon 12 Point Sockets, one each, 1/6, 1/2, 3/6, 13/2, 5/8, 11/6, 3/4, 13/6, 1/8, 11/6, 11/8 in.
1—Swing Head Handle, 151/2 in.

Cross Bar, 9 in.

Reversible Ratchet

2-Extensions, one each 51/2 in. and 10 in.

Red steel box 1811/16 x 57/8 x 31/2 in.

Per Set 1/4 AND 1/2 IN. SQUARE DRIVE



30 Piece Set

Contents:

ontents:

1/2 in. Square Drive

-Hexagon 12 Point Sockets, one each 1/16, 1/2, 1/16, 1/2, 1/16, 1/3, 1/16, 1/3, 1/16, 1/3 in.

-Speeder, 19 in.

-Swing Head Handle 151/2 in.

Cross Bar, 9 in. Reversible Ratchet

Extension, 5½ in.


14 in. Square Drive 6—Hexagon 6 Point Sockets, one each 14, 142, 156, 1142, 158, 163 3—Square 8 Point Sockets, one each 14, 16, 18 in.

Swing handle, 6 in.

1—Cross Bar, 4 in. Red steel box 19 x 65/8 x 6 in.

Per Set FX-7811-G X25D27.... .839.51One set in ctn. Wt. ctn. 16 lbs.

3/4 IN. SQUARE DRIVE



19 Piece Set

Contents: 14 Hexagon 12 Point Sockets, one each 1, 11/6, 11/8, 11/1, 15/6, 13/8, 11/6, 13/4, 11/6, 13/8, 11/6, 13/8, 11/6, 13/8, and 2 in.

Extensions, one each 4, 8 and 16 in.

Slide T handle 18 in.

Reversible Ratchet 18 in.

Red steel box 221/2 x 61/4 x 31/2 in.

Per Set

FX-7910-G X50 D05.... One set in ctm. Wt. etn. 37 lbs.

INDESTRO SELECT STEEL

Drop-Forged-Scientifically Heat-Treated-Brightly Plated

1/4 IN. HEX DRIVE



6 Piece Set

5—Sockets, one each 1/4, 1/6, 11/22, 3/8 and 7/6 in.
1—Combination spinner-extension-screw driver handle, of shock-proof tenite II U.L. approved. Sockets held on Handle.

Per Set F8044G (360) D7C8. .. \$1.23 Twelve in box. Wt. box 3 lbs.



7 Piece Set


Contents: 5-6 Point Hexagon sockets, one each 1/4, 5/16, 11/32, 3/8 and 1/16 in.

4 Point Square Socket, 1/4 in. -Round Knurled Socket, 3/8 in.

L handle, 4 in.

Red baked enamel case.

Per Set Per Set F7993G D6C6..... .. \$1.03 Twenty-four sets in ctn. Wt. ctn. 71/2 lbs.



Contents: 11 Piece Set

5—6 Point Hex Sockets, one each ¼, ¾6, ¾8, ¼6, ½ in. 2—4 Point Square Sockets, one each ¼ and ¾6 in.


1-Extension 334 in. 1-L Handle, 4 in.

Combination, spinner-screwdriver handle.
Round knurled socket, 3/8 in.

Red baked enamel case.

Per Set F8045G (367) X2D08... .. \$3.25 One set in box. Wt. box 3/4 lb.

1/4 AND 1/2 IN. HEX DRIVE



19 Piece Wall Klip Set

1/4-Inch Drive -6 point sockets, one each 1/4, 5/6, 11/22, 3/8, 7/6 in.
-4 point square sockets, one each 1/4 and 5/6 in.

-L handle, 4 in.

1/2-Inch Drive -12 point sockets, one each 1/16, 1/2, 9/16, 5/8, 11/16, 3/4, 7/8, 15/16 in.

-Ratchet Handle

L Handle

-Screw Driver Adaptor

Red baked enamel case with wall slots.

X3D48.... F7962G (1454)Three sets in box. Wt. box 23/4 lbs. 3/8 IN. HEX DRIVE



10 Piece Set

Contents: -6 point sockets, one each $\frac{9}{22}$, $\frac{5}{16}$, $\frac{11}{22}$, $\frac{3}{8}$, $\frac{7}{16}$, $\frac{15}{22}$, $\frac{1}{2}$, $\frac{9}{16}$, $\frac{5}{8}$ in. -L Handle, 6 in.

Red baked enamel case

Per Set F8043G (2104) X1D40..... \$2.19

Twelve sets in box. Wt. box 10 lbs.

1/2 IN. HEX DRIVE



7 Piece Set

Contents: 6-12 Point Sockets, one each 1/2, 9/6, 5/8, 11/16, 3/4, 7/8 in. -L handle, 61/2 in. Red baked enamel case holds sockets securely.

Per Set F8021G (1351) X1D57.....

Three sets in box. Wt. box 33/4 lbs.




8 Piece Set

Contents: -12 Point Sockets, one each 1/6, 1/2, 9/6, 5/8, 11/6, 3/4, 1/8 in. 1—L handle, 6½ in. Sockets held on L handle.

Per Set Per Set F7994G (1349) X1 D39.....

6 Sets in box. Wt. box 61/4 lbs.



11 Piece Wall Klip Set

-12 Point Sockets, one each 1/6, 1/2, 9/6, 5/8, 11/16, 3/4, 7/8, and 15/16 in.

Ratchet Handle L Handle

....\$5.40

-Screw Driver Adaptor

Red baked enamel case with wall slots.

Per Set (1453) X2D97......\$4.65 F7961G

Three in box, Wt. box 71/2 lbs

SOCKET WRENCH ATTACHMENTS

INDESTRO CHROME ALLOY

Chrome Alloy Steel—Scientifically Heat-Treated—Rich Chrome Finish Thin Wall, Hot Broached, Four-Way Lock-On Sockets

3/8 IN. SQUARE DRIVE

REGULAR SOCKETS



			Size		Wt. Box	
Each			in.	Point	lbs.	Each
F3431G	(2712)	D3C6	3/8	6	1/4	\$0.56
F3432G	(2714)	D3C6	7/16	12	1/4	. 56
F8433G	(2716)	D3C6	$\frac{1}{2}$	12	1/4	.56
F8434G	(2718)	D3C6	9/16	12	1/2	.56
F8435G	(2720)	D3C6	5/8	12	1/2	. 56
F8436G	(2722)	D4C1	11/16	12	3/4	.64
F8437G	(2724)	D4C2	3/4	12	3/4	.66
F8438G	(2726)	D5C2	13/16	12	3/4	.80
F8439G	(2728)	D5C9	7/8	12	1	.92
			Six in box			

DEEP SOCKETS



			Size		Wt. Box	
Each			in.	Peint	lbs.	Each
F8442G	(2742)	D5C3	7/16	12	1/2	\$0.82
F8443G	(2743)	D5C3	1/2	12	1/2	.82
F8444G	(2744)	D5C8	9/16	12	1/2	.90
F8445G	(2745)	D6C0	5/8	12	1	.94
F8446G	(2745)	D6C6	11/16	12	11/4	1.03
F8447G	(2747)	D7C0	3/4	12	11/2	1.08
F8448G	(2748)	D8C3	13/16	12	$1\frac{3}{4}$	1.29
	30 MI-E		Six in box.			

UNIVERSAL JOINT SOCKETS



			6 Point	
Each			Size in.	Each
F8449G	(2714UV)	X1D53	7/16	\$2.40
F8450G	(2716UV)	X1D53	$\frac{1}{2}$	2.40
F8451G	(2718UV)	X1 D53	9/16	2.40
F8452G	(2720UV)	X1D53	5/8	2.40
		Two in	box. Wt. box ¼ lb.	

REVERSIBLE RATCHETS



52 tooth action. Quick, smooth, effortless reversing. Form-fit cap for comfortable palming. A new hold every 7 degrees. Fast ratching. Length 8 inches.

Each		Each
F8414G	(2775)	X3D76\$5.88
		Four in box, Wt. box 4 lbs.


SWING HEAD HANDLES



Ball and spring tension to hold head at any selected angle. Broached \(\frac{3}{8} \) in. square opening in handle for use as extension. Also drilled for cross bar. Length 9 in.

Each			Each
F8396G	(2781)	X1D77	\$2.77
		Six in box. Wt. box 31/4 lbs.	

SPEEDER HANDLES



For speedy assembly or tear down. Designed with ball thrust bearing for easy operation and is knurled for comfortable grip. Length 16½ in.

Each		Each
F8401G	(2785)	X1D40\$2.19
		Six in box, Wt. box 5¾ lbs,

EXTENSIONS



Forged in one piece. Drilled for cross bar.

Each		Length in.	No. in Box	Wt. Box lbs.	Each
F8392G (2730) D6C4	3	6	3/4	\$1.00
F8393G (2733	D8C6	6	4	3/4	1.33
F8394G (2735) X1D03	12	4	11/2	1.62

UNIVERSAL JOINTS



Spring tension in joints holds drive at any selected angle. Length 111/16 in.

Each		Each	
F8397G	(2797)	X1D52\$2.38	
		6 in box. Wt. box 3/4 lb.	

SOCKET WRENCH ATTACHMENTS

INDESTRO CHROME ALLOY

Chrome Alloy Steel—Scientifically Heat-Treated—Rich Chrome Finish
Thin Wall, Hot Broached, Four-Way Lock-On Sockets
1/2 IN. SQUARE DRIVE

REGULAR SOCKETS



For Hexagon Nuts and Bolts

		Size	Wt. Box	
Each		in.	lbs.	Each
F8476G (1214) [04C0	7/16	3/4	\$0.61
F8477G (1216) I	04C0	1/2	3/4	.63
F8478G (1218)	04C3	9/16	3/4	.67
F8480G (1220) I	04C3	5/8	3/4	.67
F8481G (1221) I	05C0	9.16 5.8 21.32	1	.77
F8482G (1222) [05C0	11/16	1	.77
F8483G (1224) [05C4	3/4	1	.84
F8484G (1225)	05C6	25/32	11/4	.88
F8485G (1226) I	05C8	13/16	$1\frac{1}{2}$.90
F8486G (1228) [06C2	7/8	134	.96
F8487G (1230) I	06C4	15/16	2	1.00
F8489G (1232) I	D7C0	1	2	1.08
F8490G (1234) I	D7C6	11/16	21/4	1.18
F8491G (1236) D	08C2	11/8	21/2	1.28
F8492G (1240) [08C5	11/4	314	1.32
(1211)		Six in box.		

DEEP SOCKETS



12 Point
For Hexagon Nuts and Bolts

	1.01 116	Adgon Lines and	DOLES	
		Size	Wt. Box.	
		in.	lbs.	Each
(3016)	D8C4	1/2	11/2	\$1.31
(3018)	D8C5	9/16	13/4	1.32
(3020)	D8C6	5/8	13/4	1.33
(3022)	D8C6	11/16	134	1.33
(3024)	D8C6	3/4	2	1.34
(3026)	D9C5	13/16		1.48
(3028)	X1D03	7/8	21/4	1.60
(3030)	X1 D13	15/16		1.77
(3032)	X1D18	1	31/4	1.84
,		Six in box.		
	(3018) (3020) (3022) (3024) (3026) (3028) (3030)	(3016) D8C4 (3018) D8C5 (3020) D8C6 (3022) D8C6 (3024) D8C6 (3024) D8C6 (3026) D9C5 (3028) X1D03 (3030) X1D13	Size in.	(3016) D8C4

UNIVERSAL JOINTS



Provides accessibility to many difficult jobs. Close coupled and with spring tension. Length $2\frac{5}{8}$ in.

Each			Each
	(3217)	X1D48	
	()	Six in box, Wt. box 2 lbs.	

REVERSIBLE RATCHET



52 tooth engagement gives a new bite every 7 degrees and can be used in the most restricted places. Especially strong, Length $10\frac{1}{2}$ inches.

Each		Each
F8419G	(3275)	X4D39\$6.86
		Four in how Wt how 576 the

SWING HEAD HANDLE



Suitable for extra leverage and to clear obstructions. Ideal for nut spinning. Swing head permits using at many angles. Ball and spring hold head at selected angle. One piece construction, Length 15 in.

Each			Each
F8421G	(3222H)	X2D71	\$4.23
		Four in box. Wt. box 8 lbs.	

SPEEDER



For speedy nut turning. Comfortable knurled handle. Ball bearing design. Friction ball in drive end gives positive lock to socket.

Each		Each
F8426G	(3208)	X1D44\$2.25
		Four in vox, Wt. box 63/4 lbs.

SLIDE T HANDLES



Ideal for use around crowded places as head slides from one end obar to other to clear obstructions. Head will hold at any selected posif tion on bar through ball and spring tension. Length 11 inches.

Each		Each
F8423G	(3206)	X1D25\$1.95
		Four in box, Wt. box 4 lbs.

EXTENSIONS




Forged in one piece. Drilled for cross bar.

Each			Length in.	No. in box	Wt. Bex Ibs.	Each
F8415G	(3216)	D8C8	51/2	6	2	\$1.37
F8416G	(3211)	X1 D07	10	4	21/4	1.68

NEW BRITAIN MACHINE CO'S.

METEOR



With reversible ratchet and extension. For carburetors, distributors, radios, television sets. etc.

Made of highly polished chrome plated alloy steel, heat treated for strength. Sockets accurately broached. Small diameter extension for hard to get at places. Spring loaded ball on ratchet drive and extension.

Consists of:

Reversible ratchet handle with screw driver bit on reverse side, length 4 inches, four inch extension and one each 3/16, 1/12, 1/4, 1/12, 5/16, 11/12, 3/8 and 1/16 inch sockets.

Attractively packed in a blue plastic case with clear hinged cover and catch. Size 2½x4½x¾ inches thick.

1/4 Inch Square Drive

Per Set		Per Set
F8022G	(1025)	X2D80\$4.00

Loose. Wt. set 1/2 lb.

CLAMPS

HARGRAVE



Super-Junior

Small C

Forged from a good grade of steel and heat treated. Nickel plated screws with sliding pin handle. Black gun metal finish frames.

					Wt.	
		0	pens,	Dept	h Box	
Each			ins.	ins.	lbs.	Each
F471G	(50P)	D3C3	1	1	1	\$0.50
F472G	(51P)	D3C5★	1	11/2	$2\frac{1}{4}$.52
F473G	(52P)	D3C7	11/4	11/4	$2\frac{1}{2}$.56
F474G	(53P)	D3C9★	11/2	11/2	$3\frac{1}{2}$.58
F475G	(54P)	D5C2★	2	11/4	2	.78
F476G	(55P)	D6C8★	3	13/8	31/4	1.02
F477G	(56P)	D7C7	21/2	$2\frac{1}{2}$	4	1.16

50P to 53P twelve, 54P to 56P six in box

ADJUSTABLE CLAMP

C Clamp

Complete range of sizes, that are priced to compete even with the "Toy" class of clamp with which many users formerly had to be content.

Frames—Correctly designed, liberally proportioned malleable iron. Heat treated, Smooth, clean natural finish.

Screws—Steel of adequate diameter, carefully fitted; "vice-type" handle.


Swivels—Revolving, oscillating, put on to stay.

Each			Opening Capacity ins.	Depth at Throat ins.	Diam. of Screw ins.	No. in Ctn.	Wt. Ctn. lbs.	▲ Each
F481G	(1410)	D1C6	1	11/8	1/4	144	21	\$0.24
F482G	(1420)	D2C1	2	11/16	5/16	144	38	.32
F484G	(1425)	D4C0	21/2	21/2	3/8	72	46	.60
F485G	(1430)	D4C4	3	2	7/16	48	40	.66
F450G	(1440)	X1 D00	4	3	9/16	24	38	1.50
F451G	(1460)	X1 D48	6	31/2	5/8	24	64	2.22



CLAMPS

JUDD



Steel frame, red enamel finish. Good quality bright steel screw, swivel head and vise type sliding pin handle.

Each			Opens, ins.	Depth, ins.	Weight Box, lbs.	Each
F490G	(152B)	D2C5	2	7/8	4	\$0.39
F491G	(156B)	D3C9	3	13/8	8	.59
			Torolero in	h		

Twelve in box

STANDARD

HARGEAVE HARGEAVE

Carriage Makers'

Used by carriage and wagonmakers, auto body builders, repair shops, etc. Malleable frame, reinforced and shaped to give greatest strength. Large diameter steel screw, will not bend or break; has deep cut acme thread and long

bearing, insuring long life. Oscillating ball and socket tip. Forge integral wing.

			Opens,	Depth,	Wt. Box,	
Each			ins.	ins.	lbs.	▲ Each
F458G	(3)	X1D12★	3	17/8	6	\$1.65
F459G	(4)	X1 D44★	4	21/16	105/8	2.16
F460G	(5)	X1 D76	5	21/2	131/4	2.64
F461G	(6)	X2D08★	6	23/4	155/8	3.12
F446G	(8)	X3D04	8	31/4	$25\frac{1}{8}$	4.56
F447G	(10)	X4D24	10	35/8	381/4	6.36

3 to 8 six in box, 10 loose

QUILT FRAME CLAMPS SARGENT



Cast iron. Ball and socket head on screw zinc dipped.

Each F493G	(ZD132)	D2C6	Opens, ins. 11/8	Depth, ins. 13/8	Weight Box, lbs.	▲ Each \$0.39
	(ZD133)	D3C3★	23/4	13/8	5	.49
		Т	welve in box			

VISE GRIP C CLAMPS PETERSON




Special alloy steel, hardened and tempered. "Ice-Tong" jaws reach around any shape-angle iron. I beams, etc. Jaw adjustment 0 to 3¾in. Length 11 inches. Jaw adjustment 3¾ in.

Each		Each
F7992G	(11R)	X2D23\$3.35
		Twelve in ctn. wt. ctn. 22 lbs.

FRAME OR CORNER CLAMPS

LARSON



Heavy 13 gauge steel with bright finish. Fits any moulding up to $2\frac{5}{8}$ inches wide. Can be used as a saw gauge. Lies flat—nail from any position. Large frames can be held in vise. Open end has advantage of clearance for gluing, nailing, soldering, welding, brazing, etc.


For miter joint, butt corner "L" joint, "T" joint and angle joints.

Each	F	Each
F466G	X1D20\$1	1.85

Twelve in box Wt. box 11 lbs.

CORNER CLAMPS

GUNVER



Popular leader for amateur and professional, 2 inch capacity for straight or molding stock. Special cut-outs for nailing, doweling, etc. Makes accurate right angle joint.

		With Steel Grips	
Each			Each
F464G	(B198)	X1D32★	\$1.98
		Twelve in box, Wt. box 15 lbs.	

CARPENTERS' BAR CLAMPS




Improved "I" Bar

A powerful clamp having "I"-shape high carbon steel bar, size 1½x5/8x½ inch. Steel screw 1/8 inch in diameter with deep cut acme thread and long bearing, insuring long life to the clamp Case hardened thrust bearing for end of screw. Crank frame, tip and slide are malleable, slide has tempered steel dog for engaging the notches. The notches do not weaken the bar, as they are in the web instead of being cut through the flange at bottom of bar. This construction makes it possible to place the notches close together, being spaced only ½ inch apart, they permit much more rapid adjustment than is possible with the ordinary clamp.

			Weight	
	Ca	pacity,	Each,	
Each		feet	lbs.	▲ Each
O-3DC-G	X4D40★	3	75/8	\$6.60
O-4DC-G	X4D80★	4	9	7.20
O-6DC-G	X5D88	6	111/8	8.82
	Lo	oose		

HARGRAVE



Can be applied to any odd length of pipe. Black iron pipe preferred. Weight according to pressure required.


Strong analysis malleable frame, slide and top, threaded to fit standard pipe thread. Bearing for screw 13/6 inch long. Hardened steel insert in tip. Hardened steel cam trigger type slide with milled teeth, locks slide. Steel screw % inch diameter. Acme thread. All parts painted red.

Clamping surfaces are 13/4x13/4 inches.

Without Pipe Fits 3/4 inch Pipe

Each ▲ Each (600) X2D40..... F479G ..\$3.60 One in box. Wt. box 1/4 lb.

JUDD



Bright steel adjustment bar with knurled edges for sure grip. Stamped steel red adjustable upper jaw and stationary lower jaw. Bright steel adjust-ment screw and sliding bar handle.

Maximum opening of jaws 6 inches. Depth 3 inches.

Each ▲ Each

Twelve in box. Wt. box 11 lbs.

PONY



Can be applied to any odd length of 3/4-inch black pipe. Extra heavy for ordinary clamping and double extra heavy pipe is recommended where greater pressure is required.

Frame is threaded to fit standard pipe threads and the slide slips over the other end. Slide can be quickly and easily adjusted to any position on the pipe and is securely locked by hardened steel plates gripping the pipe. It will not slip.

Malleable iron castings, orange baked enamel finish. Cold drawn steel screw 5/8-inch diameter with deep smoothly cut threads. Hardened thrust bearing at point of screw. Hardened steel reversible clutch discs. Clamping face 134 inch square. One piece malleable iron handle. Baked black enamel finish.

One set consists of tail and head piece, or one complete clamp. Don't use galvanized pipe.

Without Pipe

Fits 3/4-inch Pipe

Per Set A Per Set F470G (500) X2D40★.....\$3.95 One set in box. Wt. box 21/2 lbs.

PONY



These fittings, when assembled to a length of 1/2-inch black steel pipe, threaded at both ends, provide an inexpensive, yet thoroughly practical steel bar clamp. Various lengths of black pipe, either of standard, heavy or extra heavy weight may be used and readily interchanged with a single set of fittings. The slide can be easily and quickly adjusted to any position on the pipe and is securely locked by gripping the pipe. Will not slip. The ball and socket screw is self-aligning on work which may not have parallel surfaces.

Malleable iron castings, orange baked enamel finish. Hardened steel reversible clutch discs. Cold drawn steel screw 1/2 inch in diameter with deep smoothly cut threads. Clamping faces 11/2 inch square and 1 inch diameter swivel, malleable iron hand wheel 21/8-inch diameter, black enamel

Without Pipe

Fits 1/2-inch Pipe

Per Set ▲ Per Set F492G (157B) D4C5★......\$0.70 F469G (52) X1D68★......\$2.75 One set in ctn. Wt. ctn. 11/2 lbs.

STAR * DENOTES BEST SELLER

BRACKET SETS

LARSON



Make Your Own

Build your own saw horse, picnic table and bench sets, work bench, swing set and many others. Easily built and taken apart for storage.

Heavy zinc coated steel brackets complete with 36 round head wood screws. For one or two inch lumber.


Packed in colorful box with instruction sheet for assembly.

In Sets of 4 Without Lumber

Per Set F495G (24) X1D25.....\$1.88 FX495G (24) X1 D25 - (Case lots 12 sets)

Twelve sets in ctn. Wt ctn 32 lbs.

SAW HORSE LEGS



Make your own saw horse, Self leveling clamps, attach to 2x4 or 2x6 without nails or screws. Locks tight. Easy to take apart and carry.

For carpenters, painters, plasterers, paper hangers, electricians, contractors, homes, city and state road work.

Made of 14 gauge steel. Baked red enamel finish.

In Sets of 4 Without Lumber


Per Set	11111	of Legs,	Wt.	Per Set
1-SH24-G	X6D50	24	25	\$9.80
1-SH30-G	X7D75	30	32	11.60

Hairh+

Packed in two ctns.

HAND SCREWS

JORGENSEN



Lathed steel spindles and sockets. Seasoned maple jaws. Spindles are equipped with right and left hand threads, making it very fast of adjustment.

The jaws can be adjusted to many angles to grip irregular surfaces. Glue will not adhere to the spindles.

		laws.	Opening,	Wt. Case,	
Each		ins.	ins.	lbs.	▲ Each
		(J3	(0)		
F507G	X2D40	6	3	$12\frac{1}{2}$	\$3.95
FX507G	X2D40-	-(Case	lots 6)		
			0)		- 16
F509G	X2D88	8	41/2	$12\frac{1}{2}$	4.75
FX509G	X2D88	★ —(Ca	ase lots 6)		
			1)		1.13
F510G	X3D28	★ 10	6	17	5.40
FX510G	X3D287	k(Ca	se lots 6)		
		(J	2)		
F511G	X3D807	k 12	81/2	271/2	6.25
FX511G	X3D807	├ —(Ca	se lots 6)		
		(J	4)		To le
F513G	X5D60	16	12	49	9.25
FX513G	X5D60-	-(Case	lots 6)		

BENCH SCREWS COLUMBIAN




Special double lead thread for maximum speed and positive gripping. Extra heavy screw head, thrust washer and nut casting. Hardwood handle 12 inches long. Length of screw 16 inches. Diameter 1½ inches.

Each	X3D10★\$4.65
0-11/8-G	X3D10★\$4.65

Twelve in case. Wt. case 80 lbs.

SAW HORSE BRACKETS

DALTON



Spee-Dee

Unmatched for speed, sureness and simplicity. Grips cross bar and legs securely. Saw horse will not fall apart when lifted.


Heavy gauge steel brackets with toothed jaws for a positive grip on cross bar, Exclusive flanged nail holes facilitate disassembly. Rustresistant finish.

For 2x4 inch Lumber

Per Pair		▲ Per Pair
F500G	(300)	X1D20\$1.80
FX500G	(300)	X1D20—(Case lots 12)

Twelve pairs in ctn. Wt. ctn. 27 lbs.

NU-WAY



Used for scaffolding, work benches, ping pong tables, platforms, temporary tables and many other uses. Easily set up and taken down.

Stamped from ½-inch steel, cadmium plated. For use with 2x4 inch legs and cross bar of various length.

Size 8x4x4 inches.

Without Lumber

Per Pair		▲ Per Pair
F498G	(NW)	X1D15\$1.89
FX498G	(NW)	X1D15—(Case lots 18 pairs)

One pair in box. 18 pairs in case. Wt. case 56 lbs.

SAW HORSE BRACKETS

SHAPLEIGHS



No Nails, Bolts or Screws

Converts five pieces of 2x4 lumber into a saw-horse which cannot slip or pull apart. Convenient and portable for hundreds of uses in the home, shop, stores and general use for building, platforms, scaffolding and benches.

Heavy gauge orange steel clamps 33/x73/4 inches, with cadmium plated wing nut locking device, which locks on legs and rail of lumber.


Fully Mechanical

For 2x4 inch Lumber—(Without Lumber)

Per Pair		▲ Per Pair
F501G	(801)	X2D50\$3.75
FX501G	(801)	X2D50-(Case lots 6 pairs)

Six pair in ctn. Wt. ctn. 36 lbs.

SAW HORSE BRACKETS



Pressed steel with horizontal corrugations. Designed so that the wood need only be sawed off square, all the same length, then slipped into the brackets, no beveling or joining necessary.

The plate acts as a stop and the wood is wedged against each other, making a stronger construction than all-wood horses. Assures exact angles and even setting on the floor. Finished in cadmium plate. Supplied with duplex nails and cadmium plated bolts and wing nuts for quick assembly. It takes four brackets to make one set or enough for one complete saw horse.

Per Set		Per Set
F499G	(2)	X1D19\$1.78
FX499G	(2)	X1 D19—(Case lots 12 sets)

One set in box. Twelve boxes in ctn. Wt. ctn. 30 lbs.

QUICK REFERENCE VISE CHART

COLUMBIAN Vise Catalog Numbers and the Catalog Numbers of Similar Sizes and Types of Other Manufactures.

Jaw Widths are in inches and the Closest Corresponding Sizes has been Used in each Case

Stationary Jaw Vises-Stationary Base

Jaw	COLUMBIAN		rker	Prentiss	Reed	Athol	Hollands	Simplex	Yost
Width 2½ 3 3½ 4 4½ 5 5½ 6 7 8	5021/2 503 5031/2 504 5041/2 505 5051/2 506 507 508	Superior 803 (29X) 803½ (39X) 804 (49X) 804½ (59X) 805½ (69X) 806 (79X) 807 (79½X 808 (60X)	Eclipse 952½ (101) 953 (102) 953½ (103) 954 (104) 954½ (105) 955 (106) 955½ (106½) 956 (107) 	511 (211) 512 (50) 513 (51) 514 (52) 515 (53) 516 (54) 517 (55) 518 (56) 519 (57) ()	102½ 103 103½ 104 104½ 105 105½ 106 107 108	612½ 613 613½ 614 614½ 615 615 615 616 617 618	12½ 13 13½ 14 14½ 15 15 15½ 16 17 18	31P 33P 41P 43P 51P 61P 71P 81P	102½ 103 103½ 104 104½ 105 105 106 107 108
			s	tationary Jaw	Vises—Swivel	Base			
2½ 3 3½ 4 4½ 5 5½ 6 7	6021/2 603 6031/2 604 6041/2 605 6051/2 606 607 608	823 (229X) 823½ (239X) 824 (249X) 824½ (259X) 825 () 825 (269X) 826 (279X) 827 (279¼X) (260X)	972½ (201) 973 (202) 973½ (203) 974 (204) 974½ (205) 975 (206) 975½ (206½) 976 (207) () 978 (208)	521 (212) 522 (90) 523 (91) 524 (92) 525 (93) 526 (94) 527 (95) 528 (96) 529 (97) ()	202½ 203 203½ 204 204 205 205 206 207 208	622½ 623 623½ 624 624 625 625 625½ 626 627 628	22½ 23 23½ 24 24½ 25 25 26 27 28	31S 33S 41S 43S 51S 51S 	202½ 203 203½ 204 204 205 205 206 207 208
			A	djustable Jaw	Vises—Swivel	Base			
3 3½ 4 4½ 5 5½ 6 7	403 4031/ ₂ 404 4041/ ₂ 405 4051/ ₂ 406 407 408		383 (270) 383½ (271) 384 (271½) 384½ (272) 385 (273) 385½ (274) 386 (275) 387 (240) 	502 503 (19) 504 (19½) 505 (20) 506 507 (21) 508 (22) 509 (23) ()	403 403½ 404 404½ 405 405½ 406 407 408	643 643½ 644 644½ 645 646 647	43 43½ 44 44 45 45 46 47 48	41SJ 53SJ 	42 43 44 45 46
				Combinat	ion Pipe Vises				
3½ 4½ 5 6	2031/ ₂ 2041/ ₂ 205 206		433½ (87) 434½ (88) 435 (288½) 436 (289½)	181 182 182½ 183	1C (31) 2C (32) 3C (33) 4C (34)	323½X 324½X 325X 326X	52 53 54 56	CP33 CP43	31 32 33 34
			1 (2000) 55 500	Heavy Ch	ipping Vises				
7 8½	107 1081/ ₂		·:	58	::::				99
			S		akers Vises —Stationary	Jaw			
4½	1241/2		654½ (146)	59	1241/2	4141/2	164½	42CP	504
				Swivel Base	Stationary Jav	w			
41/2:	2241/2		674½ (246)	99	2241/2	4241/2	264½		505
				Swivel Base	Adjustable Ja	w			
41/2	4241/2			26	4241/2	4441/2	4641/2		

No attempt has been made to make comparisons of quality, strength, weight or capacity.

This information is taken from the latest available catalog of each of the manufacturers mentioned above.

MACHINISTS' VISES

COLUMBIAN


These vises have many outstanding features that provide quality and economy—accuracy, greater strength and longer service.

Malleable Iron Castings—Guaranteed unbreakable—insure maxmum strength and shock resistance.

Steel Screw and Malleable Iron Nut—The design and rigid alignment provide maximum power and reduce wear. Steel balls on both ends of handle are forged from handle stock and can not come loose.

Graphite-Bronze (self-lubricating) Bearings at front of sliding jaw takes thrust of steel screw head, provides easy positive operation, prevents wear and eliminates "end play".

"T" section design, pinned into castings and will not come loose.



Stationary Base-Stationary Jaw

Designed to handle the varied sizes and weights of work in the average shop, these vises will stand the abuse often given to such a tool.

The machined flat base of Columbian vises permits firm installation with three bolts, and eliminates cutting the bench top.

Each		Width Jaws, ins.	Jaws Open, ins.	Depth Jaws, ins.	Weight Each, lbs.	Each
O-503-G	X23 D80	3	41/2	$2\frac{1}{2}$	20	\$28.00
O-5031/2-G	X27D20	31/2	51/2	$2\frac{3}{4}$	29	32.00
O-504-G	X32D30	4	6	27/8	36	38.00
O-5041/2-G	X40 D80	41/2	7	31/2	47	48.00
-1-508-G	X187 D00	8	12	51/2	150	220.00
	CHICAL					

Loose

HEAVY CHIPPING VISES

COLUMBIAN



Designed for use wherever mass weight is of primary importance.

Hardened tool steel jaw faces with machine cut diamond-shaped teeth insure firm grip on heavy work.


Kromiron castings provide increased tensile strength and greater shock resistance. Other parts same high quality material and workmanship as machinists' vises.

Stationary Base-Stationary Jaw

Jaws 8 inches wide, open 12 inches.

Each		▲ Each
+108−G	X187 D00	\$220.00

Wt. each 268 lbs.



Swivel Base-Stationary Jaw


The effective swivel base allows these vises to be swung freely and locked in any desired position, reducing the shifting of work in the vise.

The steel clamping nut draws the teeth of a forged steel lock bolt up into gear-like corrugations in the base plate—the most positive locking device.

The advantages of shifting the position of work and holding it at different angles without removing the piece from the vise are appreciated by users.

	Width Jaws, ins	Jaws Open, ins	Depth Jaws, ins	Weight Each, lbs	Each
X30D60	3	41/2	$2\frac{1}{2}$	25	\$36.00
X35D70	31/2	51/2	23/4	34	42.00
X42D50	4	6	27/8	42	50.00
X122D40	6	10	41/4	106	144.00
X238 D00	8	12	51/2	170	280.00
	X35D70 X42D50 X122D40	X35D70 3½ X42D50 4 X122D40 6	X35D70 3½ 5½ X42D50 4 6 X122D40 6 10	X30D60 3 4½ 2½ X35D70 3½ 5½ 2¾ X42D50 4 6 2⅓ X122D40 6 10 4¼	Signature Sign

Loose



These vises are made of the same high quality materials and workmarship as machinists' vises, but have high jaws and tool steel pipe jaws in addition to regular flat jaws.

The pipe jaws of tool steel are carefully heat treated to insure correct hardness and strength. The three jaws are interchangeable and each has

two working faces.

The special design of the pipe jaws makes it possible to hold down to 1/8 inch pipe without the pipe jaws protruding beyond the jaw faces. Other work can be held, therefore, without removing the pipe jaws.

Adjustable Base Stationary Jaw


Each		Width Jaws, ins.	Jaws Open, ins.	Holds Pipe, ins.	Weight Each, lbs.	▲ Each
O-2031/2-G	X44D20	$3\frac{1}{2}$	4	1/8 to 21/2	36	\$52.00
0-2041/2-G	X62D90	41/2	5	1/8 to 31/2	60	74.00
			Loose			

Equalize Freight with nearest Jobber carrying Columbian Vises

Items Marked - Not Carried in Stock. Can Only be Furnished by Shipping Direct from Factory, F. O. B., Cleveland, Ohio

WORKSHOP VISES

COLUMBIAN




Heavy duty front jaw beam of channel steel, covering screw. Extra large back jaw, anvil and anvil horn. Cold rolled steel screw. Handle balls forged from handle stock. Replaceable malleable iron nut with Acme thread and heat treated steel jaw faces. Permanent pipe jaws, positive tri-grip design. Positive locking swivel base with slip handle lock nut. Bright red finish with polished jaws and anvil.

Swivel Base

Specifications:

	Jaws,	Open,	Capacity	
Nos.	in.	in.	in.	
D433/2	31/2	4	1/8 to 11/4	
D44	4	5	1/8 to 2	
D45	5	6	1/8 to 21/2	
F 1		Wt. Each, lbs.	▲ Each	
Each		IDS.	A Each	
O-D431/2-G	X8D33★	171/2	\$12.50	
O-D44-G	X12D13★	30	18.20	
O-D45-G	X15D33	48	22.70	

One in ctn.



Extra heavy steel beam with balanced castings

for super strength.

Large back jaw anvil and anvil horn. Coldrolled steel screw. Slip-proof screw collar. Handle balls forged from handle stock and "3-point" Tri-Grip permanent pipe jaws. Positive locking swivel base, with slip-handle lock nut. Polished jaws and anvil with bright Colum! ian red finish.

Swivel Base

Replaceable Steel Jaw Faces


Width of jaws 31/4 inches. Jaws open 4 inches. Depth 11/4 inches. Pipe capacity 1/4 to 11/4 inches.

Each		▲ Each
0-D331/2-G	X5D67★	\$8.50

One in ctn. Wt. ctn. 13 lbs.

WORKSHOP VISES

COLUMBIAN



RED ARROW

Extra heavy steel beam with balanced castings for super strength.

Large back jaw anvil and anvil horn. Coldrolled steel screw. Slip-proof screw collar. Handle balls forged from handle stock and "3-point" Tri-Grip permanent pipe jaws. Positive locking swivel base, with slip-handle lock nut. Polished jaws and anvil with bright Columbian red finish.

Smooth Jaw Faces

Swivel Base


Width of jaws 3½ inches. Jaws open 4 inches. Pipe capacity ½ to 1¼ inches.

Each		▲ Each
O-D631/2-G	X5D25★	\$7.90

One in ctn. Wt. ctn. 13 lbs.

HOMESHOP VISE

COLUMBIAN



SWIVEL BASE

Steel screw, slide bar and handle. Anvil back. Pipe jaws. Replaceable steel jaw faces. Polished jaws and anvil.

Width of jaws $3\frac{1}{2}$ inches. Opens 3 inches. Pipe capacity $\frac{1}{8}$ to 1 inch.

Each			Each
0-31/2-G	X4D00★		.\$6.00
	One in ctn.	Wt. ctn. 10 lbs.	

VISES

B & C



Unexcelled for ordinary jobs about the home, garage or farm.

Fine grain gray iron frame and front section. Anvil back. Accurately machined, hardened and polished jaws. Nickel plated feed screw and two supporting rods. Steel sliding handle on feed screw and bench clamp. Red baked enamel finish.

Width of jaws 13/4 inches. Jaws open 13/4 inches.

Each			▲ Each
F7233G	(149)	X1D24★	\$1.88

One in box. Wt. box 2 lbs.



Fine grain gray iron frame and anvil back, red baked enamel finish. Accurately machined jaws, polished and lacquered. Machine cut feed screw with nickel plated head and sliding steel handle. Two nickel plated supporting rods. Steel bench clamp screw with nickel plated head and sliding steel handle.

Width of jaws 21/2 inches. Opens 21/2 inches. Bench clamp screw opens 21/4 inches.

Each		▲ Each
F7236G	(150/21/2)	X2D03★\$3.06

One in box. Wt. box 32/3 lbs

WOODWORKERS' VISES



Bench Type


Cast iron construction. Solid steel screw and sliding handles. Clamp screw with wing nut.

Jaws 5x51/2 inches, opens up to 31/2 inches.

Each		Each
0-165-G	X2D35★	 \$3.2

One in ctn. Wt. ctn. 5 lbs.

STANDARD



Bench

For home, farm and school workshop, hobbyists and craftsmen.

Iron web design double jaw construction for full parallel bearing surface. Screw holes in jaws for attaching hardwood facings. Well fitting square cut screws and 1/2 inch steel guide rods. Strong steel handle-bar of convenient length. Screw holes for attaching to both the front and underside of bench.

Jaws 51/2 inches wide, 15/8 inches deep. Maximum opening 41/2 inches.


Each			Each
F7232G	(134)	X2D30	\$3.45

One in box, twelve in ctn. Wt. ctn. 51 lbs.

STAR * DENOTES BEST SELLER

WOODWORKER'S

STANLEY-HANDYMAN



For Work Bench or Saw Horse

Light weight portable clamp vise with presswood face plate. Jaws 5-inch wide horizontally, 43%-inches wide vertically "L" shaped jaws open to 31/2-inches. Sliding steel handle. Steel screw bench clamp with sliding steel handle.

Each		▲ Each
F7237G	(700)	X5D00 ★\$7.50


One in box. Wt. box 55/8 lbs.

WOODWORKERS' VISES

COLUMBIAN

For general use in woodworking or manual training shops. Simple in construction. Durable, reliable and smooth in operation.

Close-grained gray iron castings, with smooth jaws drilled for wood facings. Cold rolled steel guide rods operate through accurately machined guides in back jaw and keeps jaws in alignment, fitted with removable lock nuts. Heavy steel screw with machine-cut double fast-running threads for positive action and maximum speed.




Continuous Screw

Steel handle socket with large head screw for securing hardwood handle.

	Wi	th Plain F	ront Jaw		
Each 0-7CPW-G	X16D00	Size Jaws, ins. 4x7	Jaws Open, ins. 9	Wt. Ctn., Ibs. 22	▲ Each \$24.00
	Wit	h Dog in I	Front Jaw		
0-7CDW-G	X16D66	4x7	9	23	25.00

One in ctn.



Rapid Acting

For shops where time is an important factor—particularly where large change in jaw opening must be made frequently.

Operation—When handle of vise is turned to left against a stop, the front jaw can be slid to full opening—a partial turn of the handle tightens the vise against the work.

Plain Front Jaw

Size Jaws,	Jaws Open,	Weight Ctn.,	
inches	inches	lbs.	▲ Each
4×10	12	32	\$29.00

With Dog in Front Jaw

4x10

One in ctn.

0-10RDW-G X20D00

WOODCRAFT VISES




A well-made, moderately priced woodworker's vise for homeshop work bench.

Close-grained gray iron castings with smooth jaws drilled for wood facings. Steel guide rods keep jaws in alignment. Steel screw with machine-cut threads insure positive free action. Steel handle socket, with hardwood handle. Will fit any bench up to 21/4 inches without mortising. Jaw 3 x 6 inches. Opens 7 inches.

Each	▲ Each
0-6C-G	X4D67★\$7.00
	One in ctn Wt ctn 10 lbs

CARPENTERS' VISES



Excellent for home workshops. Light weight. Can be carried in tool kit.


30.00

Aluminum with nickel plated screw parts. 5x5 inch aluminum alloy jaws. Horizontal and vertical faces hold work in any position. Jaws open 3½ inches to hold 2x4 wood securely. Tool steel feed screws and guide pin. Fits popular 2¼ inch bench top.

Holes in jaws for mounting wood faces.

Note-Equalize Freight with Nearest Jobber Carrying Columbian Vises

ELECTRIC FORGES



For homecraft service and general repair work. Steel hearth. Sturdy motor, without radio interference. Blast regulated by damper on intake. Fully braced steel pipe legs. Toggle switch on fan case. Complete with 10 foot cord and attachment plug.

Operates on 110 volt, 60 cycles, single phase.

With Half Hood-10 inch Fan

Size 24x35 inches. Height 30 inches

Each		Each
+4143S-K	X136D00	\$200.00

One in crate. Wt. crate 145 lbs.

With Shield-8 inch Fan

Diameter of hearth 18 inches. Height 30 inches.

Each	Each
+4145S-K	X61 D00\$92.00
	One in crate Wt crate 45 lbs



For home workshops, schools, industrial and farm. Fuel storage space beneath the hearth. Upper door in base receives the fuel and automatically feeds it to the lower storage reservoir from which it is removed for use.

Steel hearth, half hood and base. Sturdy motor, without radio interference. Eight inch fan. Blast regulated by damper on intake side. Toggle switch on fan case. Complete with attachment cord and plug.

Diameter of hearth 18 inches. Height 30 inches.

Operates on 110 volts, 60 cycles, single phase.

Each	Eac	h
-1146SE-K	X120 D90	1()

One in crate. Wt. crate 55 lbs.

ANVILS



VULCAN

BLACKSMITHS'

Face of solid tool steel, tempered, ground and polished and welded to the body by a special process. Horn and point are covered with tough untempered steel. Body is made of best quality gray iron.

DIRECT SHIPMENT

F. O. B., Chattanooga, Tenn.

Each		Weight, lbs.	Face, ins.	Height Overall, ins.	Horn, ins.	Hardie Hole, ins.
4-V7-K	X27D95	70	3½x11	8¼	734	3/4
+ V10-K	X34D85	100	$3\frac{1}{2}$ x $12\frac{1}{2}$	$9\frac{1}{2}$	73/4	1∕8
-₩V13-K	X40 D00	130	$3\frac{3}{4} \times 13\frac{1}{2}$	103%	81/8	1
-+V15−K	X47D50	150	$4x14\frac{1}{2}$	11¼	81/8	1
+V20−K	X62 D50	200	4½x16	121/4	93/4	11/8

Wrapped in burlap

BLACKSMITHS' HOOF PARERS

SHAPLEIGHS



Full polished head. Black finish handles, forged from highest grade tool steel. Oil tempered jaws. Length 14 ins.

Each			Each
F7008G	(100/14)	X2D33★	\$3.50
		Six in hox Wt hox 1216 lbs.	

FARRIERS' KNIVES



High carbon steel blade, uniformly tempered and highly polished. Solid adjustable iron

handle. Blade 4 inches long, 3/4 inches wide. Handle 41/2 inches long.

Each		Each
S1505A	(10F)	X1D90★\$2.95
		Twelve in how Wt how 4 lbs

BLACKSMITHS' APRONS



Muleskin, Without Bib

Gray color. Two-piece. Double seamed and riveted to split. Size 26x34 inches.

Each	Each
P-M-G	X6D65\$10.00
	Loose, Wt. each 21/4 lbs.

WELDING COMPOUND



E-Z

Used between laps of welds. For welding all grades of steel.

5 lbs. In Wood Box

Per Box		Per Box
F7383G	(3)	X1D15★\$1.75
		Sold only in full boxes.

TINNERS' SNIPS



Duckbill or Circular Pattern Hollow Ground

High carbon hot drop forged steel, scientifically heat-treated. Hardened slab bolt, special lock nut. Hollow ground blades, full polished, rust inhibitor treated. Large positive stop. Hard chrome finish blade area. Red baked enamel handles.

Each		Over-all Lgth., in.	Cut,	Wt. Box, lbs.	Each
F7453G	X1D70	7.50	13/4	1/2	\$2.60
F7452G	X2D20	10	21/2	1	3.30
F7451G	X2D75	121/2	3	15/8	4.10

One in box.





Straight-Hollow Ground

High carbon hot drop forged steel, scientifically heat-treated. Hardened slab bolt, special locknut. Hollow ground blades, full polished, rust inhibitor treated. Large positive stop. Hard chrome finish blade area. Red baked enamel handles.

		Over-all		Wt.	
		Lgth.,	Cut,	Box,	
Each		ins.	ins.	lbs.	Each
F7438G	X1D67	7	13/4	1/2	\$2.50
F7439G	X2D10	10	21/2	1 -	3.10
F7440G	X2D50	123/4	3	13/4	3.70
		One in l	ox.		

WISS



Straight

Crucible steel inlaid blades. Gun metal finish handles. Wt.

Each			Cut, ins.	Lgth, ins.	Box,	▲ Each
F7462G	(W7)	X5D00	4	141/2	3	\$7.50
		X4D67				

One in box

Metal Master

Hot drop forged of Molybdenum alloy steel, blades precisely hardened and tempered. Nickel chrome Molybdenum bolts. Compound leverage action.


Unexcelled for cutting intricate patterns in sheet metal, air conditioning ducts, louvres, roofing, eaves, gutters, auto body repair, aircraft manufacturing equipment, installation and steel strapping.



Cuts Left

Length of cut 13% inches. Over all length 10 inches.

▲ Each Each F7464G (WM1) X2D83★.....\$4.25 One in box. Wt. box 3/4 lb.



Cuts Right

Length of cut 13/8 inches. Over all length 10


▲ Each Each F7465G (WM2) X2D83★.....\$4.25 One in box. Wt. box 34 lb.



Combination

Length of cut 11/2 inches. Over all length 10 inches.

Each ▲ Each F7466G (WM3) X2D83★..... One in box. Wt. box 3/4 lb.



Bulldog Combination

Length of cut 1 inch. Over all length 91/2 inches.


Each (WM5) X2D83★..... F7467G One in box. Wt. box 34 lb.

STAR * DENOTES BEST SELLER

MIDWEST



Straight



Drop forged from special high carbon steel, heat treated. Blades machine hollow ground and polished. Gray enameled handles. Smoothly finished.

Straight

			Cut, I	Lgth.	Wt. Box	. V
Each			ins.	ins.	lbs.	▲ Each
F7426G	(77 S)	X1D30	$1\frac{3}{4}$	7	1/2	\$1.95
F7427G	(107S)	X1D67★	21/2	10	1	2.50
F7428G	(127S)	X2D00★	33/4	12	$1\frac{3}{4}$	3.00
		One in	box.			

Duckbill or Circular

Each			Cut,	Size,	Wt. Box lbs.	▲ Each
F7432G	(77D)	X1D30	134	7	1/2	\$1.96
F7433G	(107D)	X1D80	$2\frac{1}{2}$	10	1	2.70
F7434G	(127D)	X2D34	3	121/2	13/8	3.50
		One in	box.			