


(No Model.)

W. G. AVERY.
SAW SET AND PUNCH.

No. 282,600.

Patented Aug. 7, 1883.



Witness,

A. B. Allen.

J. R. Tibbitts.

Inventor,

William G. Avery,

By Geo. W. Tibbitts, Atty.

UNITED STATES PATENT OFFICE.

WILLIAM G. AVERY, OF CLEVELAND, OHIO.

SAW-SET AND PUNCH.

SPECIFICATION forming part of Letters Patent No. 282,600, dated August 7, 1882.

Application filed October 12, 1882. (No model.)

To all whom it may concern:

Be it known that I, WILLIAM G. AVERY, of Cleveland, in the county of Cuyahoga and State of Ohio, have invented certain new and useful Improvements in Saw-Sets, of which the following is a specification.

In the accompanying drawing, the figure is a side elevation of my improved saw-set.

A is a jaw with a handle, which is the foundation or support for the working parts. It is chambered nearly its whole length, and provided with ears *d d*, in which are pivoted the handle-lever B and the gripping-jaw C. The lever B at its inner end engages with the inner end of the gripping-jaw. A spring, *s*, secured to handle A, operates to force the handles apart when released. The jaw A has a slanting face and forms the anvil upon which the saw-blade lies. Said jaw is also provided with an adjustable gage or guide, *g*, to adjust the tool to different sizes of saw-teeth. The movable or gripping jaw C is provided with a die, D, which grips the saw-tooth and bends it over the angle of the anvil A. Said jaw is also provided with a thumb-screw, *d*, for gagging the throw of the die. E is a hollow punch

adjustably fixed in said jaw C, to be used, when desired, for punching leather. The punch is held in place by a set-screw, *e*, so that the punch may be reversed in position, as seen in dotted lines, when not required for use. This renders this tool useful for two purposes, the jaw A serving as the surface against which the punch works in cutting.

Having described my invention, I claim—

1. The improved saw-set, consisting of the anvil-jaw A, with its chambered handle, having ears *d d* and spring *s*, and provided with the adjustable gage *g*, the lever-handle B, and the movable gripping-jaw C, having die D and gage thumb-screw *d*, constructed, combined, and operating substantially as specified.

2. The combination, with the jaw C, of the saw-set, and the cutting-punch E, adjustably fixed and held by the thumb-screw *e*, for punching leather in conjunction with the jaw A, substantially as specified.

WILLIAM G. AVERY.

Witnesses:

E. W. LAIRD,

GEO. W. TIBBITTS.